

Rectangular Multipole - continued

Mini-Clamp Series - continued

2mm Pitch, Wire-to-Wire and Wire-to-Board - continued

366919

Colour	Mftrs. List No.	Order Code	Price Each		
			1+	50+	100+
Mini Clamp - Plugs					
Green	37104-2124-000 FL	100801-4213	177.00	158.00	142.00
Blue	37104-2165-000 FL	100801-4221	180.00	160.00	144.00
Grey	37104-2206-000 FL	100801-4230	182.00	162.00	146.00
Mini Clamp - Sockets					
Green	37304-2124-000 FL	100801-4248	192.00	171.00	154.00
Blue	37304-2165-000 FL	100801-4256	192.00	171.00	154.00
Grey	37304-2206-000 FL	100801-4264	192.00	171.00	154.00
Green with Latch	37304-2124-0P0 FL	100801-4272	192.00	171.00	154.00
Blue with Latch	37304-2165-0P0 FL	100801-4280	192.00	171.00	154.00
Grey with Latch	37304-2206-0P0 FL	100801-4299	192.00	171.00	154.00
4 Way, with Boardlock	37204-62B3-004 SC	801-4302	218.00	194.00	174.00
4 x 4 Way, no Boardlock	37216-62M3-004 SC	801-4310	332.00	296.00	266.00

Link Connector

2.54mm Pitch, Wire-to-Wire Hermaphroditic



- Uses IDC termination for reliable connection
- Links network systems together by 'Tapping' into the cables
- 4 position single row, accommodates 18 AWG flat ribbon cable or discrete wire
- Simple operation by general purpose pliers
- Latching mechanism - secure location
- Meets CC Link Association specifications
- UL Recognised

Current Rating	5.0A	Withstand Voltage	1000V for 1 Minute (382 Series)
Voltage Rating	160V	Operating Temperature	-20°C to +70°C
Insulation Resistance	1MR @ 500V dc	Wire Size	2.54mm (0.1") Flat cable
Withstand Voltage	1000V rms @ sea level		

366920

Mftrs. List No.	Order Code	1+	50+	100+
Wiremount Link connector				
38104-0018-000 FL 100	801-4329	253.00	226.00	203.00
Boardmount Receptacle, Right Angle				
38204-52S3-000PL	NEW 953-9352	257.00	228.00	205.00
Boardmount Receptacle, Straight				
38204-62S3-000PL	NEW 953-9360	196.00	174.00	157.00

JWPF Waterproof Connector



Compact waterproof wire to wire connector system

- Housing Lock for secure mating
- Double Leaf Contact Construction
- IP67 Rating

Current Rating	3.0A AC DC	Plating	Tin
Pitch	2.0mm	Housing	Nylon
Voltage	100V AC DC	Applicable Wire	AWG 26 to 22
Contacts	Phosphor Bronze - Female Brass - Male	Temperature Range	OD 1.4mm to 1.74mm -25°C to +85°C

231761

No of Ways	Mftrs. List No.	Order Code	5+	25+	50+	100+	+
Receptacle Housing Assembly							
2	02R-JWPF-VLSE-S	384-9806	51.00	48.00	46.00	42.00	--
3	03R-JWPF-VLSE-S	384-9820	58.00	55.00	53.00	48.00	--
4	04R-JWPF-VLSE-S	384-9843	59.00	56.00	53.00	48.00	--
Tab Housing Assembly							
2	02T-JWPF-VLSE-S	384-9818	106.00	101.00	96.00	86.00	--
3	03T-JWPF-VLSE-S	384-9831	118.00	112.00	106.00	96.00	--
4	04T-JWPF-VLSE-S	384-9855	123.00	117.00	110.00	100.00	--
			Price Each				
			10+	100+	500+	1K+	
Contacts for JWPF							
Socket	SWPR-001T-P025	384-9788	6.00	6.00	6.00	5.00	
Tab	SWPT-001T-025	384-9790	5.00	5.00	5.00	4.00	
			Price Each				
			1+				
Crimp Tool	WC-JWPF	434-1430	17,497.00				
Extraction Tool	EJ-JWPF	434-1442	14,560.00				

Sealed Connector System



MX150L™ Series



The MX150L sealed connector system is designed to meet the needs for a rugged, environmentally sealed connector system supporting both low-level signal applications and power applications up to 18A. With the MX150L connector, completing the application is as simple as crimping the appropriate terminal, poking it into place and plugging the housings together. There is no need for additional application of individual wire seals.

Crimp terminals Can be provided either on a strip or loose. A "long" version is available where a first-mate last-break terminal is required for hot plug applications.

- Environmentally sealed to IP67 and USCAR-2, Rev. 3 standards
- Integrated mat wire seal
- Integrated interface seal
- Simple crimp and poke application
- Supports 22-18 and 16-14 AWG wire range

Dielectric withstand voltage	1500V ac	Contacts - Current Max.	
Insulation resistance	1000MR	Operating temperature	-40°C to 125°C
Contacts - Voltage Max.			

347336

No. of Ways	Wire Range AWG	Mftrs List No.	Order Code	1+	50+	100+	500+
MX150L Plug							
2	22 - 18	0194190008	732-2836	321.00	286.00	252.00	222.00
2	16 - 14	0194190007	732-2828	321.00	287.00	251.00	221.00
4	22 - 18	0194190005	732-2852	292.00	260.00	228.00	201.00
4	16 - 14	0194190004	732-2844	292.00	261.00	228.00	201.00
6	22 - 18	0194190012	732-2879	354.00	315.00	278.00	245.00
6	16 - 14	0194190011	732-2860	354.00	315.00	278.00	245.00
8	16 - 14	0194190002	732-2895	354.00	315.00	278.00	245.00
8	22 - 18	0194190001	732-2887	354.00	317.00	278.00	244.00
10	22 - 18	0194190015	732-2917	466.00	414.00	366.00	322.00
10	16 - 14	0194190014	732-2909	466.00	417.00	365.00	321.00
12	22 - 18	0194190017	101-3190	485.00	414.00	347.00	334.00
12	16 - 14	0194190018	101-3192	485.00	414.00	347.00	334.00
16	22 - 18	0194190020	101-3193	574.00	489.00	409.00	394.00
16	16 - 14	0194190021	101-3194	574.00	489.00	409.00	394.00
MX150L Receptacle							
2	22 - 18	0194180008	732-2739	362.00	322.00	284.00	250.00
2	16 - 14	0194180007	732-2720	362.00	324.00	284.00	250.00
4	22 - 18	0194180005	732-2755	331.00	294.00	260.00	228.00
4	16 - 14	0194180004	732-2747	331.00	295.00	259.00	228.00
6	22 - 18	0194180011	732-2771	409.00	364.00	321.00	283.00
6	16 - 14	0194180010	732-2763	409.00	364.00	321.00	283.00
8	16 - 14	0194180002	732-2798	407.00	362.00	319.00	281.00
8	22 - 18	0194180001	732-2780	407.00	364.00	318.00	281.00
10	22 - 18	0194180014	732-2810	515.00	458.00	404.00	356.00
10	16 - 14	0194180013	732-2801	516.00	461.00	404.00	355.00
12	22 - 18	0194180026	101-3186	546.00	467.00	391.00	376.00
12	16 - 14	0194180027	101-3187	546.00	467.00	391.00	376.00
16	22 - 18	0194180029	101-3188	638.00	546.00	456.00	438.00
16	16 - 14	0194180030	101-3189	638.00	546.00	456.00	438.00
Terminal - Male							
				Order Multiple=10		Price Per Terminal	
				10+	50+	100+	500+
Strip	22 - 18	0194170024	732-2674	7.00	6.00	5.00	5.00
Strip	16 - 14	0194170011	732-2666	7.00	6.00	5.00	5.00
Loose	22 - 18	0194170048	732-2690	8.00	7.00	6.00	6.00
Loose	16 - 14	0194170047	732-2682	7.00	6.00	6.00	5.00
Loose, Long	22 - 18	0194170052	732-2712	8.00	7.00	6.00	6.00
Loose, Long	16 - 14	0194170051	732-2704	8.00	7.00	6.00	6.00
Terminal - Female							
				Order Multiple=10		Price Per Terminal	
				10+	50+	100+	500+
Strip	22 - 18	0194200002	732-2933	6.00	6.00	5.00	4.00
Strip	16 - 14	0194200001	732-2925	6.00	6.00	5.00	4.00
Loose	22 - 18	0194200010	732-2950	7.00	7.00	6.00	5.00
Loose	16 - 14	0194200009	732-2941	6.00	6.00	5.00	5.00
Hand tools							
				Price Each			
				1+			
Extractor		638131500	732-2968	1,685.00			
Crimper - Male Terminal		638114000					
Crimper - Female Terminal		638113900	732-2984	25,815.00			
			732-2976	25,815.00			

Sealed Connector System



MX150L™ Series

Panel Mount Plugs and PCB Headers



- Environmentally sealed to IP67 when mated
- Integrated terminal position assurance (TPA)
- Field serviceable contact removal system
- Simple crimp and poke application
- Supports 22-18 and 16-14 AWG wire range
- Mates with 19418 series receptacles



414171

No. of Ways	Mftrs List No.	Order Code	1+	50+	100+	500+
Plug - Panel Mount						
2	194290026	965-3708	100.00	90.00	81.00	79.00
4	194290025	965-3716	205.00	184.00	164.00	158.00
6	194290028	965-3724	132.00	118.00	105.00	102.00
8	194290029	965-3732	137.00	122.00	110.00	106.00

Prices are in Thai Baht and exclude 7% VAT. Due to the volatile nature of certain products, prices are subject to change without notice.