

Test Lead Wire

Flexivolt - 2V 1500V, CAT III
258/0.07mm (1.0mm²) - Double insulated



- Fine stranded plain copper conductors with double layered highly flexible reinforced PVC insulation. Neutral inner with coloured outer for high safety requirements
- Designed for operating voltages in **Overvoltage Category III**
- **UL 94 - HB** recognised

Nominal outside dia. 3.9mm Current rating **19A**
Voltage rating 1500V Operating temperature -10°C to +60°C
Test Voltage 8000V

Mfrs. List No. 7030X, where X = 1-black, 2-red, 3-blue, 4-yellow, 5-green, 8-white

208100

5m Coils		Price Per Coil/Reel			
Colour	Order Code	1+	5+	+	+
Red	611-372	790.00	740.00	--	--
Black	611-384	759.00	711.00	--	--
Green	611-396	790.00	740.00	--	--
Blue	611-402	790.00	740.00	--	--
Yellow	611-414	790.00	740.00	--	--
25m Reels					
Red	611-438	3,991.00	3,736.00	--	--
Black	611-440	3,991.00	3,736.00	--	--
Green	611-451	3,991.00	3,736.00	--	--
Blue	611-463	3,838.00	3,592.00	--	--
Yellow	611-475	3,991.00	3,736.00	--	--
White	611-487	3,991.00	3,736.00	--	--

Silivolt - 1V 1500V, CAT II

512/0.05 (1.0mm²) - Halogen Free Silicone Insulated



- Fine stranded plain copper conductors with highly flexible reinforced halogen free silicone insulation. Chlorine content <4ppm conforming with **DIN VDE 0472, pt 813**.
- Designed for operating voltages in **Overvoltage Category II**
- **UL 94-HB** recognised

Nominal outside dia. 3.7mm Operating temperature -80°C to +150°C (cont.)
Voltage rating (Cat II) 1500V -80°C to +250°C (4 hrs.)
Test Voltage 8000V Soldering iron resistant +300°C (10 secs.)
Current rating **19A**

Mfrs. List No. 7607X, where X = 1-black, 2-red, 3-blue, 4-yellow, 5-green, 8-white

208101

5m Coils		Price Per Coil/Reel			
Colour	Order Code	1+	5+	+	+
Red	119-0627	1,466.00	1,386.00	--	--
Black	119-0628	1,466.00	1,386.00	--	--
White	119-0629	1,466.00	1,386.00	--	--
25m Reels					
Red	119-0630	7,211.00	6,807.00	--	--
Black	119-0631	7,211.00	6,807.00	--	--
Green	119-0632	7,211.00	6,807.00	--	--
Blue	119-0633	7,211.00	6,807.00	--	--
White	119-0634	7,211.00	6,807.00	--	--

PVC - Double Insulated - 1500V CAT II

651/0.07mm (2.5mm²)



- Fine stranded plain copper conductors with soft PVC double insulation to produce a highly flexible wire as used for Multi-Contact ready made test leads, see **Book 4, Section 22**
- Available in Red or Black with White inner insulation.

Nominal outside dia. 4mm Current rating **32A**
Voltage rating 1500V Operating temperature -10°C to +70°C
Test Voltage 8000V

Mfrs. List No. 22.0130-1 = 297-756/218-054, 22.0130-4 = 297-768/218-066

207974

5m Coils		Price Per Coil/Reel			
Colour	Order Code	1+	5+	+	+
Red	297-756	869.00	831.00	--	--
Black	297-768	869.00	831.00	--	--
25m Reels					
Red	218-054	4,431.00	4,162.00	--	--
Black	218-066	4,431.00	4,162.00	--	--

'Plast' - 2V

525/0.07mm (2.0mm²)



- Fine stranded plain copper conductors
- Thermoplastic rubber, double insulated
- Operates over a wide temperature range
- Excellent flexibility

Nominal outside dia. 3.9mm Test Voltage 8000V
Voltage rating 1500V Operating temperature -30°C to +110°C (cont.)
Current rating **30A**

207975

5m Coils		Price Per Coil/Reel			
Colour	Order Code	1+	5+	+	+
Red	365-3006	859.00	763.00	--	--
Black	365-3018	859.00	763.00	--	--
25m Reels					
Red	365-3020	4,126.00	3,668.00	--	--
Black	365-3031	4,126.00	3,668.00	--	--

Mains Flex - 2-Core

2192Y (Har. code H03VVH2-F2)
Two-Core Oval 300/300V



Flexible mains cable for internal use in the direct connection of equipment to mains power supplies.

- PVC insulated and sheathed flexible mains cords
- Standard core colours, Brown & Blue
- Available in Black, Grey or White outer sheath
- Manufactured to BS6500
- Supplied in 100m reels or continuous length in 1m multiples

Conductor Area (mm²) 0.5 Current Rating **3A** Nominal Dia. 3.3 x 5.4mm
0.75 **6A** 3.6 x 5.8mm

		Price Per Reel			
Colour	Order Code	1+	5+	+	+
3A 100m Reel					
Black	721-270	1,309.00	1,232.00	--	--
Grey	721-281	1,309.00	1,232.00	--	--
White	721-293	1,309.00	1,232.00	--	--
6A 100m Reel					
Black	721-300	1,722.00	1,544.00	--	--
Grey	721-311	1,722.00	1,544.00	--	--
White	721-323	1,722.00	1,544.00	--	--

335144

Continuous Length in 1m Multiples		Price Per Metre	
Colour	Order Code	1+	
3A			
Black	385-2738	19.00	
Grey	385-2740	19.00	
White	385-2751	19.00	
6A			
Black	385-2763	23.00	
Grey	385-2775	23.00	
White	385-2787	23.00	

2182Y (Har. code H03VV-F2)

Two-Core Round 300/300V



- PVC insulated and sheathed flexible mains cords
- Standard core colours, Brown & Blue
- Available in Black, Grey or White outer sheath
- Manufactured to BS6500
- Supplied in 100m reels

Conductor Area (mm²) 0.5 Current Rating **3A** Nominal Dia. 5.4
0.75 **6A** 5.8

Compliant Non-compliant
● ▲ Limited stock - RoHS replacement available



300,000 products, stocked and ready to despatch