

Mains Extension Leads - continued

Cable Reels - continued

Mfrs. List No.	Description
6015	Large PVC cassette 10M 240V 6A
7010	Standard PVC cassette with handle 10M 240V 6A
7035	Standard PVC cassette with handle 9M 110V 16A
8005	PVC drum cable reel with steel frame 25M 240V 13A
8025	PVC drum cable reel with steel frame 50M 240V 13A with overload cut-out
8035	PVC drum cable reel with steel frame 25M 240V 13A

209286

Mfrs. List No.	Order Code	1+	5+	10+
6015	307-3520 ◊	1,112.00	918.00	898.00
7035	307-3555	1,602.00	1,338.00	--
8005	307-3567 ◊	2,347.00	1,936.00	1,894.00
8025	307-3592 ◊	3,713.00	2,885.00	2,500.00
8035	307-3609 ◊	3,242.00	2,518.00	2,392.00

◊ Fits UK 3 Pin Mains Socket

Industrial BS4343

Industrial Connectors from



An Extensive Range of Industrial Plugs and Sockets which conforms to all the relevant standards: **BS 4343:1992**, **BSEN 60309-2**, **IEC 309** and **CEE 17**.

- Colour coded for Voltage Identification: Yellow=110 Volts (100-130V), Blue=230 Volts (200-250V), Red=400 Volts (380-415V)
- All moulded parts, except flexible grommets, are produced from high quality plastic material which is self-extinguishing and free from cadmium and halogen. High impact temperature of -25°C to +40°C and up to +50°C under load
- Each terminal fitted with two screws for extra safe and secure connection
- Terminal screws left friction fit in open position for speedy wiring
- Extended earth terminal for quick positive identification
- All free plugs and sockets come with internal strain relief for secure cable retention. Also moveable for ease of wiring
- All sockets fitted with spring loaded covers for added protection when not in use
- All Panel/Chassis mounting sockets come complete with gasket
- All 63 amp and 125 amp have additional matching pilot contact in accordance with the relevant standards

213788

Free Plugs, IP44

Straight



- Conforms to **BS4343**, **EN60309 1 & 2** and **CEE17**
- Long grommet clearly marked with cable diameter sizes for best fit

Voltage & Amps	Number of Poles	Mfrs. List No.	Order Code	1+	5+	10+	25+
110V, 16A	2P+E	210304	723-2100 ●	246.00	222.00	208.00	184.00
230V, 16A	2P+E	210306	843-623 ●	235.00	212.00	201.00	177.00
400V, 16A	3P+E	210406	723-2111 ●	449.00	404.00	382.00	337.00
400V, 16A	3P+N+E	210	843-520 ●	502.00	481.00	461.00	417.00
110V, 32A	2P+E	230304	715-9523 ●	632.00	613.00	595.00	566.00
230V, 32A	2P+E	230306	716-0458 ●	653.00	633.00	614.00	582.00
400V, 32A	3P+E	230406	716-1323 ●	668.00	640.00	614.00	569.00
400V, 32A	3P+N+E	230	716-1785 ●	698.00	673.00	650.00	613.00

Phase-Changeover Plug

Two of the phase-Pins are mounted on an insulated base which can be quickly and easily rotated to change motor direction thereby avoiding the time consuming necessity to re-wire the plug.

213789

Phase Changer	Poles	Mfrs. List No.	Order Code	1+	5+	10+	25+
400V,16A	3P+N+E	210PH	843-660 ●	1,568.00	1,412.00	1,333.00	1,177.00

Switched Interlocked Sockets

IP44 and IP67



- Supplied complete with PG - Metric adaptors where applicable
- Fully interlocked cannot be switched 'On' until correct plug is fully inserted
- Plug cannot be removed until the switch is in the 'Off' position
- Padlockable

213801

Voltage & Amps	Poles	Mfrs. List No.	Order Code	1+	5+	10+	25+
IP44							
110V,16A	2P+E	5312314	723-2731 ●	5,136.00	4,623.00	4,639.00	4,253.00
230V,16A	2P+E	5312316	723-2743 ●	5,136.00	4,623.00	4,639.00	4,253.00
400V,16A	3P+E	5312416	718-3367 ●	5,917.00	5,745.00	5,595.00	5,334.00
400V,16A	3P+N+E	5312516	718-3392 ●	6,140.00	5,980.00	5,839.00	5,596.00
110V,32A	2P+E	5312334	723-2755 ●	7,069.00	6,362.00	6,385.00	6,049.00
230V,32A	2P+E	5312336	718-3586 ●	7,114.00	6,936.00	6,817.00	6,522.00
400V,32A	3P+E	5312436	718-3598 ●	7,608.00	7,401.00	7,219.00	6,906.00
400V,32A	3P+N+E	5312536	718-3604 ●	7,895.00	7,694.00	7,518.00	7,213.00
IP67							
110V,16A	2P+E	5313314	723-2767 ●	6,619.00	5,958.00	5,978.00	5,592.00
230V,16A	2P+E	5313316	723-2779 ●	6,619.00	5,958.00	5,978.00	5,592.00
400V,16A	3P+E	5313416	723-2780 ●	6,782.00	6,104.00	6,126.00	5,707.00
400V,16A	3P+N+E	5313516	723-2792 ●	7,114.00	6,403.00	6,425.00	6,011.00
230V,32A	2P+E	5313336	723-2809 ●	7,474.00	6,727.00	6,750.00	6,315.00
400V,32A	3P+E	5313436	723-2810 ●	7,806.00	7,026.00	7,050.00	6,620.00
400V,32A	3P+N+E	5313536	723-2822 ●	8,038.00	7,234.00	7,260.00	6,772.00
IP67							
230V,63A	2P+E	5313366	723-2834 ●	15,770.00	14,193.00	13,720.00	13,418.00
400V,63A	3P+E	5313466	716-6515 ●	12,853.00	12,527.00	12,240.00	11,745.00
400V,63A	3P+N+E	5313566	716-6618 ●	13,594.00	13,258.00	12,962.00	12,452.00

3 Way Long Plastic Box

IP44



- 16A, 2P+E, complete with 2m cable, plug and handle

213805

Voltage	Mfrs. List No.	Order Code	1+	5+	10+	25+
110V	6532314P2	723-3085 ●	6,228.00	5,605.00	5,624.00	5,318.00
230V	6532316P2	723-3097 ●	6,228.00	5,605.00	5,624.00	5,318.00
110V+ 25A, 2P, RCD	6532314P2R	723-3103 ●	12,931.00	11,639.00	11,679.00	11,213.00
230V+ 25A, 2P, RCD	6532316PR	723-3115 ●	12,931.00	11,639.00	11,679.00	11,213.00

Mains Leads

13A Plug Lead, 2m/3m

Black, Grey or White



- High quality non-rewireable cable assemblies
- Meets harmonised European standard **BS4491.EN60.320**
- Choice of 2m or 3m of 1.0mm² cable approved to **BASEC BS6500**
- Plug fitted with a 13A fuse and manufactured to **ASTA BS1363A**
- IEC socket approved to **BSI, VDE, NFUSE, OVE, CEBEC, NEMKO, DEMKO, SEMKO, SETI, IMQ, SEV and KEMA-KEUR**

Body length=65 (straight) 45 (right angle) ,
Cable length=2m or 3m

Current rating	10A @ 250V ac	Cable and connector housings	PVC
Fuse supplied	13A (interchangeable)	Plug contacts	Brass
		Socket contacts	Phosphor Bronze

Warning:The fuse supplied is designed to protect the cord set only. The appliance should be protected separately.