

No. of Ways	Order Code	1+	10+	50+	+	+	+
50° Entry							
9	118-8169	618.00	546.00	429.00	--	--	--
15	118-8170	657.00	581.00	454.00	--	--	--
25	118-8171	653.00	573.00	451.00	--	--	--
37	118-8172	723.00	636.00	500.00	--	--	--
50	118-8312	778.00	701.00	546.00	--	--	--
Male Screwlock							
Recessed slotted	118-8177	24.00	21.00	17.00	12.00	--	--
Finger jackscrew	118-8176	120.00	107.00	82.00	57.00	--	--

Metallised Plastic
Straight and 45° Cable Entry



- ABS with nickel over copper plating
- EMC/RFI shielding braid/foil folded back over suitable size strain relief bush
- Range of 5 strain relief bushes per hood
- Accepts foil, lap or braided cable
- No tooling required for shield termination

Shell Dimensions	H	H	W	D	Cable Entry via 5 Bushes
	Straight	45°	Both	Both	
9 way	35.5	37.2	31.1	16.3	5 - 7.5
15 way	38.8	40.6	39.1	16.3	5 - 8
25 way	42	44.1	53.1	18	5 - 8
37 way	46.5	47.5	69.3	23	8 - 15

No. of Ways	Straight Entry Order Code	45° Entry Order Code	1+	10+	50+	+	+
9	746-058	746-060	212.00	204.00	192.00	--	--
15	746-071	746-083	224.00	214.00	203.00	--	--
25	746-095	746-101	248.00	236.00	224.00	--	--
37	746-113	746-125	345.00	330.00	312.00	--	--

Metallised Plastic
Metal Plated Plastic Shield Hoods



- For HDP20 and HDE20 metal shell connectors
- Housing: Thermoplastic nickel plated over copper
- 4-40 screws: Steel, zinc plated
- Jackscrews: Steel, zinc plated clear chromate

No. of Ways	Mfrs. List No.	Order Code	1+	25+	100+	250+
9	748677-1	140-2640	277.00	248.00	188.00	141.00
9	5748677-1	109-8416	827.00	740.00	560.00	420.00
15	748677-2	140-2651	377.00	337.00	271.00	223.00
15	5748677-2	109-8417	506.00	452.00	342.00	257.00
25	748677-3	140-2663	233.00	208.00	177.00	147.00
25	5748677-3	109-8418	357.00	319.00	242.00	181.00

Metallised Plastic
Straight and 45° Cable Entry



- Low profile 45° design
- Turned, full metal 4-40 thumb screws
- Plastic strain relief inserts for cable sizes 3.5mm to 13mm
- ABS with nickel over copper plating
- No tooling required for shielded termination

Mfrs. List No: MHD45PKx-K = 45° Hood MHDTPKx-K = Top Entry Hood, Where x = No. of ways

No. of Ways	45° Entry Order Code	Top Entry Order Code	1+	10+	50+	+	+
9	357-649	357-728	141.00	134.00	126.00	--	--
15	357-662	357-765	136.00	129.00	121.00	--	--
25	357-698	357-698	141.00	134.00	126.00	--	--
37	357-704	357-984	165.00	158.00	151.00	--	--

Die-Cast Backshells
For D-Subminiature connectors



Suitable for high integrity data links in computer peripheral, medical and instrumentation applications

- Straight or 45° cable entry
- Excellent EMI/RFI Shielding
- Lightweight and cost effective
- Supplied with standard cable grommet
- High performance cable grommet available for 360° screening
- Tooling and dies required for high performance grommet

Contact material	Phosphor Bronze	Contact material	Phosphor Bronze
Contact plating	Gold plated	Insulator material	PBT UL94V-0
Temperature range	-40°C/120°C to	Shell	Zinc Die Cast

No. of Ways	Mfrs. List No.	Order Code	1+	25+	100+
Top Entry Backshells					
9 way	0-1478762-9	412-9696	170.00	146.00	126.00
15 way	1-1478762-5	412-9702	171.00	146.00	134.00
25 way	2-1478762-5	412-9714	180.00	156.00	134.00
37 way	3-1478762-7	412-9726	217.00	181.00	156.00
45° Angled entry Backshells					
9 way	0-1478763-9	412-9738	170.00	146.00	134.00
15 way	1-1478763-5	412-9740	171.00	146.00	134.00
25 way	2-1478763-5	412-9751	180.00	156.00	143.00
37 way	3-1478763-7	412-9763	217.00	181.00	156.00
High Performance Screened Cable Grommet					
6.0 mm	0-1478764-1	412-9775	71.00	62.00	57.00
7.5mm	0-1478764-2	412-9787	77.00	64.00	59.00
8.5mm	0-1478764-3	412-9799	76.00	66.00	57.00
9.5mm	0-1478764-4	412-9805	84.00	70.00	60.00
Crimp Tool and Dies for Screened Cable Grommet					
Crimp Tool	6-1419172-9	412-9817	7,302.00		
Die sets					
6.0mm	0-1583684-1	412-9829	1,153.00		
9.5mm	0-1583684-4	412-9854	1,153.00		

Diecast Rapid Assembly



- Nickel plated die cast covers
- High quality plastic capped UNC440 jackscrews
- Rapid assembly strain relief insert
- 360° shielding
- Fully tapped screw holes
- Phillips headed screws

No. of Ways	H	W	D
9	39.9	31.2	15.0
15	41.5	39.5	15.3
25	48.6	53.4	15.5
37	53.6	69.7	15.5

No. of Ways	Order Code	1+	10+	50+	+	+
Nickel						
9	486-1693	162.00	153.00	143.00	--	--
15	486-1700	203.00	190.00	180.00	--	--
25	486-1711	191.00	170.00	159.00	--	--
37	486-1723	253.00	223.00	200.00	--	--

Diecast Rapid Assembly Hi-Grade



- Nickel plated die cast covers
- High quality plastic capped UNC440 jackscrews
- Rapid assembly strain relief insert
- 360° Metallised shielding
- Metallised shielding greatly enhances the performance of the hood
- Fully tapped screw holes
- Phillips headed screws

No. of Ways	H	W	D
9	39.9	31.2	15.0
15	41.5	39.5	15.3
25	48.6	53.4	15.5
37	53.6	69.7	15.5