

Voltage	Order Code	Price Each				
		1+	5+	10+	15+	+
92mm, Standard						
115V	960-0523	2,205.00	2,161.00	2,095.00	1,984.00	--
230V	960-0531	2,205.00	2,161.00	2,095.00	1,984.00	--
115V	960-0540	2,261.00	2,216.00	2,171.00	2,128.00	--
230V	960-0558	2,425.00	2,380.00	2,304.00	2,182.00	--
119mm, Super Low Noise						
115V	959-9789	2,053.00	1,951.00	1,853.00	1,760.00	--
230V	959-9770	2,277.00	2,243.00	2,166.00	1,979.00	--
119mm, Low Noise						
115V	959-9738	2,158.00	2,128.00	1,944.00	1,801.00	--
230V	959-9746	2,153.00	1,941.00	1,831.00	1,616.00	--
119mm, Standard						
115V	959-9703	1,880.00	1,781.00	1,680.00	1,519.00	--
230V	959-9711	1,880.00	1,781.00	1,680.00	1,519.00	--
115V	960-1511	2,843.00	2,820.00	2,733.00	2,632.00	--
230V	960-1520	2,843.00	2,820.00	2,733.00	2,632.00	--
610mm Connecting Lead						
	959-9720	151.00	140.00	139.00	136.00	--

80mm, 120mm



- UL94V-0 plastic impeller and diecast aluminium casing
- Shielded ball bearings
- Impedance protected
- Connection via two 0.11" terminals
- UL recognised, CSA approved

Fan size	60mm	80mm	120mm	150mm
Cut-out Ø	58.5	77	114.5	151
Fix Centres	50	71.5	105	162
Fix. hole Ø	4.3	4	4.3	4.3

Dimensions H W D	Voltage V ac	Power Watts	Air Flow cu ft/min	Noise dBA@1m	Mfrs. List No.	Order Code
60 60 30	115	4.5	7.0	29	2412PS-12W-B30-A00	101-2734
80 80 38	230	10	26.5	33	3115PS-23T-B30-A00	942-0177
120 120 38	230	15	95.3	37	4715MS-23T-B5A-A00	942-0185
150 172 38	230	35	176.5	56	5915PC-23T-B30-A00	101-2742

Dimensions H W D		Voltage ac	Order Code	1+	10+	25+	50+	+
60	60	30	115	NEW 101-2734	1,654.00	1,502.00	1,379.00	1,298.00
80	80	38	230	NEW 942-0177	1,539.00	1,385.00	1,285.00	1,134.00
120	120	38	230	NEW 942-0185	1,713.00	1,542.00	1,431.00	1,262.00
150	172	38	230	NEW 101-2742	5,509.00	5,304.00	4,993.00	4,371.00

80mm, 119mm



- Low cost, low noise, high pressure fans
- Impedance protected
- Sleeve bearings
- Diecast aluminium zinc housings
- UL94V-0 rated plastic impellers
- Supplied with 300mm, 22 AWG lead wire
- Approved to TUV, UL recognised and CSA

Operating temperature -10°C to +70°C Life expectancy >30000 hours @ 55°C

Voltage V ac	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA@1m	Bearing Type	Order Code
80mm, Standard						
115	12	30	14.1	35	SB	926-061
230	14	30	14.1	35	Ball	371-9741
119mm, Low Noise						
115	11	76	35.8	38	SB	926-085
230	11	76	35.8	38	SB	926-097
119mm, Standard						
115	18	105	49.5	48	SB	926-103
230	18	107	50.4	50	SB	926-115

	80mm	119mm
Height	80	119
Width	80	119
Depth	38	38
Cut-out Ø	77	116
Fix Centres	71.5 x 71.5	105 x 105
Fix Centres Ø	4.3	4.3

Voltage	Order Code	Price Each			
		1+	10+	25+	50+
80mm, Standard					
115V	926-061	1,285.00	1,164.00	1,080.00	915.00
230V	371-9741	550.00	508.00	485.00	471.00
119mm, Low Noise					
115V	926-085	1,262.00	1,145.00	1,064.00	915.00
230V	926-097	1,262.00	1,145.00	1,064.00	915.00
119mm, Standard					
115V	926-103	1,331.00	1,264.00	1,189.00	1,045.00
230V	926-115	1,331.00	1,264.00	1,189.00	1,045.00

160mm



- Efficient, low noise fans
- Thermally protected shaded pole motor.
- VDE approved, UL recognised, CSA certified
- Fitted with ball bearings.

Life expectancy >50000 hours

Dia=150, D=55
Cut-out Ø=147
Fix. Centres=162 x 4.5

Voltage V ac	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA@1m	Operating Temp °C	Lead Length	Mfrs. List No.	Order Code
110	39	232	109	52	-30 to +65	330	W2S130-AA25-01	959-9894
240	40	206	97	49	-30 to +65	330	W2S130-AA03-01	959-9908
110/240	40	206	97	49	-30 to +65	330	W2S130-AA03-49	959-9916

Voltage	Order Code	Price Each			
		1+	5+	10+	15+
110V	959-9894	3,191.00	2,883.00	2,793.00	--
240V	959-9908	3,107.00	2,799.00	2,793.00	--
110/240	959-9916	4,874.00	4,290.00	4,022.00	3,856.00

171mm Maltese AC



- Die-cast venturi, with UL94-V0 flame retardant polypropylene impeller
- Air intake over the fan struts
- Stainless steel ball bearings
- Termination via two pin terminal
- 53,000 hours fan life at 40°C, L₁₀
- UL recognised, CSA and VDE approved

Voltage V ac	Frequency Hz	Current A	Power Watts	Noise dBA@1m	Speed RPM	Air Flow cu ft/min	Mfrs. List No.	Order Code
230	50/60	0.2/0.18	40.5/41.4	56.5	2850/3400	250/300	MA77B3	444-5600
115	50/60	0.33/0.36	50/60	56.5	2850/3350	250/300	MA2B3	444-5612

Dimensions H W D		Voltage V	Order Code	1+	5+	10+	25+	+
171.5	150.4	55	230	444-5600	5,306.00	4,856.00	4,443.00	4,113.00
171.5	150.44	55	115	444-5612	5,306.00	4,856.00	4,720.00	4,370.00

Voltage V ac	Frequency Hz	Current A	Power Watts	Noise dBA@1m	Speed RPM	Air Flow cu ft/min	Mfrs. List No.	Order Code
230	50/60	0.2/0.18	40.5/41.4	56.5	2850/3400	250/300	MA77B3 031844	102-3677
115	50/60	0.33/0.36	50/60	56.5	2850/3350	250/300	MA2B3 031842	102-3678

Dimensions H W D		Voltage V	Order Code	1+	5+	10+	25+	+
171.5	150.4	55	230	102-3677	5,306.00	4,856.00	4,443.00	4,113.00
171.5	150.44	55	115	102-3678	5,306.00	4,856.00	4,443.00	4,113.00

171mm 'Falcon'



- Feathered edge impeller for low noise
- Stainless steel ball bearings
- Die-cast aluminium alloy venturi with flame retardant polycarbonate propeller
- CSA and VDE approved, UL recognised

Voltage V ac	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA@1m	Mfrs. List No.	Order Code
115	41	250	118	54.8	FA2B32	162-5597
240	40.5	250	118	54.8	FA77B3 31660	162-5585

10

Fans

Compliant Non-compliant Limited stock - RoHS replacement available

RoHS