

Table with columns: Dimensions (L, W, H), Case Size, Mfrs. List No., Order Code. Rows include 25 Volt d.c. and 35 Volt d.c. capacitor specifications.

Table with columns: Dimensions (H, Dia.), DC Leakage Current (µA), Impedance (Ω) @ 100kHz 20°C, Mfrs. List No., Order Code. Rows include 16 Volt d.c. capacitor specifications.

Table with columns: Order Code, Price Each (1+, 50+, 100+, 500+, +). Rows include 6.3 Volt d.c., 10 Volt d.c., 16 Volt d.c., 20 Volt d.c., and 25 Volt d.c. capacitor specifications.

Table with columns: Order Code, Price Each (5+, 50+, 100+, 500+, +). Rows include 16 Volt d.c. capacitor specifications.

Table with columns: Dimensions (H, Dia.), DC Leakage Current (µA), Impedance (Ω) @ 100kHz 20°C, Mfrs. List No., Order Code. Rows include 25 Volt d.c. capacitor specifications.

Table with columns: Order Code, Price Each (5+, 50+, 100+, 500+, +). Rows include 25 Volt d.c. capacitor specifications.

Table with columns: Dimensions (H, Dia.), DC Leakage Current (µA), Impedance (Ω) @ 100kHz 20°C, Mfrs. List No., Order Code. Rows include 35 Volt d.c. capacitor specifications.

Table with columns: Order Code, Price Each (5+, 50+, 100+, 500+, +). Rows include 35 Volt d.c. capacitor specifications.

CB Series



- General purpose
● Wide temperature range
● Resin dipped tantalum capacitors

Lead dia. = 0.5, Lead pitch = 5.0
Operating temperature -55/125°C to +2°C
Tolerance ±20%


Table with columns: Dimensions (H, Dia.), DC Leakage Current (µA), Impedance (Ω) @ 100kHz 20°C, Mfrs. List No., Order Code. Rows include 6.3 Volt d.c. capacitor specifications.

Table with columns: Order Code, Price Each (5+, 50+, 100+, 500+, +). Rows include 6.3 Volt d.c. capacitor specifications.

Table with columns: Dimensions (H, Dia.), DC Leakage Current (µA), Impedance (Ω) @ 100kHz 20°C, Mfrs. List No., Order Code. Rows include 10 Volt d.c. capacitor specifications.

Table with columns: Order Code, Price Each (5+, 50+, 100+, 500+, +). Rows include 10 Volt d.c. capacitor specifications.

TAP Series - Professional Resin Dipped



Lead dia. = 0.5
Lead pitch = 5.0

Operating temperature -55°C± to +85°C at rated voltage
Climatic category 55/125/56
Tolerance ±20%

Table with columns: Dimensions (H, Dia.), DC Leakage Current (µA), Impedance (Ω) @ 100kHz 20°C, Mfrs. List No., Order Code. Rows include 6.3 Volt d.c. capacitor specifications.

Capacitors

15

Compliant
Non-compliant
RoHS
Limited stock - RoHS replacement available