


**20 x 5mm Fuses - continued**

**Quick Blow (F) Glass**  
20 x 5mm Fuses S500 Series\*



- Complies with **IEC127, BS4265, Standard Sheet II**
- Approved to **SEMKO, BSI, VDE, IMQ**
- **UL** recognised\* except 8A and 10A which are not approved


Voltage rating (Vn) 250V ac  
Breaking capacity 35A @ Vn

Mftrs. List No. 50mA to 6.3A S500 + Rating,  
8A, 10A\* TDC641 + Rating

204592

Rating	Order Code	Price Each				
		10+	250+	500+	1K+	+
50mA	112-3089	37.00	34.00	32.00	29.00	--
63mA	112-3093	37.00	34.00	31.00	30.00	--
80mA	112-3095	37.00	34.00	31.00	30.00	--
100mA	112-3074	27.00	25.00	23.00	21.00	--
125mA	112-3077	23.00	21.00	19.00	18.00	--
160mA	112-3078	6.00	6.00	5.00	5.00	--
200mA	112-3081	6.00	6.00	5.00	5.00	--
250mA	112-3082	6.00	6.00	5.00	5.00	--
315mA	112-3085	6.00	6.00	5.00	5.00	--
400mA	112-3086	6.00	6.00	5.00	5.00	--
500mA	112-3088	6.00	5.00	5.00	5.00	--
630mA	112-3092	6.00	6.00	5.00	5.00	--
800mA	112-3094	6.00	6.00	5.00	5.00	--
1A	112-3079	6.00	6.00	5.00	5.00	--
1.25A	112-3072	6.00	6.00	5.00	5.00	--
1.6A	112-3073	6.00	6.00	5.00	5.00	--
2A	112-3083	6.00	6.00	5.00	5.00	--
2.5A	112-3080	6.00	6.00	5.00	5.00	--
3.15A	112-3084	6.00	6.00	5.00	5.00	--
5A	112-3090	6.00	6.00	5.00	5.00	--
6.3A	112-3091	6.00	5.00	5.00	5.00	--
8A	112-3096	5.00	4.00	4.00	4.00	--
10A	112-3076	5.00	4.00	4.00	4.00	--

**Antisurge(T) HRC Ceramic**  
S505 Series



- Complies with **IEC127, Standard Sheet V**
- Approved to **VDE (2A to 5A), SEMKO (1.6A to 4A)**

Voltage rating (Vn) 250V ac  
Breaking capacity 1500A @ Vn

Mftrs. List No. Single: S505 + Rating

204611

Order Multiple=10

Rating	Order Code	Price Each				
		10+	250+	500+	1K+	+
500mA	112-3121	29.00	28.00	27.00	26.00	--
800mA	112-3124	29.00	28.00	27.00	26.00	--
1A	112-3115	11.00	10.00	10.00	9.00	--
1.25A	112-3112	11.00	10.00	10.00	9.00	--
1.6A	112-3113	11.00	10.00	10.00	9.00	--
2A	112-3118	11.00	10.00	10.00	9.00	--
2.5A	112-3116	11.00	10.00	10.00	9.00	--
3.15A	112-3119	11.00	10.00	10.00	9.00	--
4A	112-3120	11.00	10.00	10.00	9.00	--
5A	112-3122	11.00	10.00	10.00	9.00	--
6.3A	112-3123	11.00	10.00	10.00	9.00	--
8A	112-3125	11.00	10.00	10.00	9.00	--
10A	112-3114	11.00	10.00	10.00	9.00	--

**Antisurge (T) HRC Ceramic**  
20 x 5mm Fuses MCF03C Series



- Complies with **IEC127, DIN41662 and BS4265**

Voltage rating 250V Breaking capacity 1500A @ 250V

Mftrs. List No. MCF03C + Rating

204487

Current Rating	Order Code	Price Each				
		10+	100+	500+	1K+	+
500mA	112-3136	16.00	15.00	14.00	12.00	--
630mA	112-3139	19.00	18.00	16.00	14.00	--
800mA	112-3140	16.00	15.00	14.00	12.00	--
1A	112-3131	16.00	15.00	14.00	12.00	--
1.25A	112-3126	16.00	15.00	14.00	12.00	--
1.6A	112-3127	16.00	15.00	14.00	12.00	--
2A	112-3133	16.00	15.00	14.00	12.00	--
2.5A	112-3132	16.00	15.00	14.00	12.00	--
3.15A	112-3134	16.00	15.00	14.00	12.00	--
4A	112-3135	16.00	15.00	14.00	12.00	--
5A	112-3137	16.00	15.00	14.00	12.00	--
6.3A	112-3138	16.00	15.00	14.00	12.00	--
8A	112-3141	16.00	15.00	14.00	12.00	--
10A	112-3128	16.00	15.00	14.00	12.00	--

**Antisurge (T) Glass**



20 x 5mm Fuses MCF06G Series



- Complies with **IEC127, DIN41662 and BS4265**


Mftrs. List No. MCF06G + rating

Voltage rating 250V  
Breaking capacity 32MA to 3.15A, 35A @ 250V, 4A to 6.3A 10 x IN @250V

204488

Current Rating	Order Code	Price Each				
		10+	100+	500+	1K+	+
32mA	112-3202	43.00	40.00	34.00	25.00	--
40mA	112-3204	43.00	40.00	34.00	25.00	--
50mA	112-3207	44.00	41.00	35.00	26.00	--
63mA	112-3213	44.00	41.00	35.00	26.00	--
80mA	112-3215	37.00	34.00	30.00	24.00	--
100mA	112-3190	44.00	41.00	35.00	26.00	--
125mA	112-3193	15.00	14.00	12.00	9.00	--
160mA	112-3194	16.00	14.00	13.00	10.00	--
200mA	112-3197	14.00	13.00	11.00	8.00	--
250mA	112-3198	10.00	9.00	8.00	6.00	--
315mA	112-3201	9.00	8.00	7.00	5.00	--
400mA	112-3203	9.00	8.00	7.00	5.00	--
500mA	112-3206	9.00	8.00	7.00	5.00	--
630mA	112-3212	9.00	8.00	7.00	5.00	--
800mA	112-3214	9.00	8.00	7.00	5.00	--
1A	112-3195	9.00	8.00	7.00	5.00	--
1.25A	112-3188	9.00	8.00	7.00	5.00	--
1.6A	112-3189	9.00	8.00	7.00	5.00	--
2A	112-3199	9.00	8.00	7.00	5.00	--
2.5A	112-3196	9.00	8.00	7.00	5.00	--
3.15A	112-3200	9.00	8.00	7.00	5.00	--
4A	112-3205	10.00	9.00	8.00	5.00	--
5A	112-3209	10.00	9.00	8.00	6.00	--
6.3A	112-3211	10.00	9.00	8.00	6.00	--
10A	112-3192	10.00	9.00	8.00	6.00	--

**Antisurge (T) Glass - Spiral Element**



S504 Series



- Complies with **IEC127, BS4265, Standard Sheet III**
- Approved to **BSI, SIMKO, VDE and IMQ**

Voltage rating (Vn): 250V ac  
Breaking capacity: 35A @ 250V ac, 50Hz, pf = 1.0  
Mftrs. List No. Single: S504 + Rating

FUS10X/204368

Rating	Order Code	Price Each			
		10+	100+	500+	1K+
50mA	534-031	47.00	42.00	36.00	29.00
63mA	534-043	47.00	42.00	36.00	29.00
80mA	534-055	49.00	44.00	38.00	30.00
100mA	534-067	18.00	17.00	15.00	11.00
125mA	534-079	18.00	17.00	15.00	11.00
160mA	534-080	18.00	17.00	15.00	11.00
200mA	534-092	18.00	17.00	15.00	11.00
250mA	534-109	12.00	10.00	9.00	7.00
315mA	534-110	12.00	10.00	9.00	7.00
400mA	534-122	12.00	10.00	9.00	7.00
500mA	534-134	12.00	10.00	9.00	7.00
630mA	534-146	17.00	10.00	9.00	7.00
800mA	534-158	12.00	10.00	9.00	7.00
1A	534-160	12.00	10.00	9.00	7.00
1.25A	534-171	12.00	10.00	9.00	7.00
1.6A	534-183	12.00	10.00	9.00	7.00
2A	534-195	12.00	10.00	9.00	7.00
2.5A	534-201	12.00	10.00	9.00	7.00
3.15A	534-213	12.00	10.00	9.00	7.00
5A	534-225	12.00	10.00	9.00	7.00
6.3A	534-237	12.00	10.00	9.00	7.00

**20 x 5mm Panel Mount Fuseholders**

Finger Release/Screw Cap



- Moulded in black phenolic with solder tab terminations

L (overall)=35.8  
Dia (bezel)=15.2  
Depth behind panel=26.5  
Panel cutout=12.9  
Panel keyway=1.7 x 1.1  
Panel thickness=3.6 max

Rating 6.3A @ 250V ac Operating temperature -55°C to +70°C  
Breakdown voltage ≥4kV (sea-level)

204525