


Male PCB Mounting Header (Optional Long Latches)
Low Profile - Class II



- Straight and 90° pins
- Low profile space saving design
- Optional snap in long latches for sockets using strain relief clip

208963

No. of Ways	Mftrs. List No.	Order Code	1+	10+	50+	100+	+	+
90° Pins								
10	2510-5002	972-551 ▲	100.00	83.00	81.00	70.00	--	--
10	N2510-5002RB	983-8350 ●	100.00	83.00	76.00	66.00	--	--
14	2514-5002	972-563 ▲	116.00	97.00	89.00	82.00	--	--
14	N2514-5002RB	983-8368 ●	116.00	97.00	89.00	77.00	--	--
16	2516-5002	972-575 ▲	123.00	102.00	94.00	86.00	--	--
16	N2516-5002RB	983-8376 ●	123.00	102.00	94.00	86.00	--	--
20	2520-5002	972-587 ▲	127.00	106.00	97.00	89.00	--	--
20	N2520-5002RB	983-8384 ●	127.00	106.00	97.00	84.00	--	--
24	2524-5002	326-7192 ▲	168.00	140.00	129.00	118.00	--	--
24	N2524-5002RB	983-8465 ●	168.00	140.00	129.00	111.00	--	--
26	2526-5002	972-599 ▲	168.00	140.00	129.00	118.00	--	--
26	N2526-5002RB	983-8392 ●	168.00	140.00	129.00	111.00	--	--
30	2530-5002	326-7209 ▲	179.00	149.00	137.00	126.00	--	--
30	N2530-5002RB	983-8473 ●	179.00	149.00	137.00	118.00	--	--
34	2534-5002	972-605 ▲	187.00	156.00	143.00	132.00	--	--
34	N2534-5002RB	983-8406 ●	187.00	156.00	143.00	132.00	--	--
40	2540-5002	972-617 ▲	196.00	163.00	150.00	137.00	--	--
40	N2540-5002RB	983-8414 ●	196.00	163.00	150.00	137.00	--	--
60	2560-5002	972-630 ▲	267.00	222.00	217.00	198.00	--	--
60	N2560-5002RB	983-8422 ●	267.00	222.00	204.00	176.00	--	--
Straight Pins								
10	2510-6002	468-885 ▲	100.00	83.00	76.00	70.00	--	--
10	N2510-6002RB	983-8244 ●	100.00	83.00	76.00	66.00	--	--
14	2514-6002	468-897 ▲	116.00	97.00	89.00	82.00	--	--
14	N2514-6002RB	983-8252 ●	116.00	97.00	89.00	82.00	--	--
16	2516-6002	468-903 ▲	123.00	102.00	94.00	86.00	--	--
16	N2516-6002RB	983-8260 ●	123.00	102.00	94.00	86.00	--	--
20	2520-6002	468-915 ▲	127.00	106.00	97.00	89.00	--	--
20	N2520-6002RB	983-8279 ●	127.00	106.00	97.00	84.00	--	--
24	2524-6002	326-7210 ▲	158.00	132.00	121.00	111.00	--	--
24	N2524-6002RB	983-8481 ●	158.00	132.00	121.00	104.00	--	--
26	2526-6002	468-927 ▲	168.00	140.00	129.00	118.00	--	--
26	N2526-6002RB	983-8287 ●	168.00	140.00	129.00	111.00	--	--
30	2530-6002	727-600 ▲	181.00	151.00	139.00	120.00	--	--
30	N2530-6002RB	983-8333 ●	181.00	151.00	139.00	120.00	--	--
34	2534-6002	468-939 ▲	187.00	156.00	143.00	132.00	--	--
34	N2534-6002RB	983-8295 ●	187.00	156.00	143.00	132.00	--	--
40	2540-6002	468-940 ▲	196.00	163.00	150.00	137.00	--	--
40	N2540-6002RB	983-8309 ●	196.00	163.00	150.00	137.00	--	--
50	2550-6002	468-952 ▲	219.00	182.00	167.00	154.00	--	--
50	N2550-6002RB	983-8317 ●	219.00	182.00	178.00	162.00	--	--
60	2560-6002	468-964 ▲	267.00	222.00	204.00	188.00	--	--
60	N2560-6002RB	983-8325 ●	267.00	250.00	230.00	221.00	--	--
64	2564-6002	727-611 ▲	304.00	253.00	247.00	226.00	--	--
64	N2564-6002RB	983-8341 ●	304.00	253.00	232.00	201.00	--	--
Long Snap-in Latches								
		Order Code			Price Per Pack			
					1+	10+	50+	
Pack 20 (for 10 headers)		587-576 ●			342.00	291.00	276.00	

Male PCB Mounting Header (Optional Long Latches)
Low Profile - Class III



- All types will accommodate both bump and click polarisation.
- Optional long latches for sockets using strain relief

208962

No. of Ways	Mftrs. List No.	Order Code	1+	10+	50+	100+	+	+
90° Pins								
10	2510-5002UG	443-396 ▲	79.00	66.00	64.00	56.00	--	--
16	2516-5002UG	443-440 ▲	98.00	81.00	75.00	69.00	--	--
20	2520-5002UG	443-451 ▲	100.00	83.00	76.00	70.00	--	--
26	2526-5002UG	443-463 ▲	112.00	93.00	86.00	79.00	--	--
34	2534-5002UG	443-610 ▲	131.00	109.00	100.00	92.00	--	--
40	2540-5002UG	443-621 ▲	148.00	123.00	120.00	110.00	--	--
Straight Pins								
10	2510-6002UG	443-657 ▲	79.00	66.00	60.00	56.00	--	--
14	2514-6002UG	443-694 ▲	96.00	80.00	73.00	67.00	--	--
16	2516-6002UG	443-700 ▲	98.00	81.00	80.00	69.00	--	--
20	2520-6002UG	443-712 ▲	100.00	83.00	76.00	70.00	--	--
26	2526-6002UG	443-785 ▲	112.00	93.00	86.00	79.00	--	--
34	2534-6002UG	443-815 ▲	131.00	109.00	100.00	92.00	--	--
40	2540-6002UG	443-827 ▲	148.00	123.00	113.00	104.00	--	--
50	2550-6002UG	443-839 ▲	172.00	144.00	132.00	121.00	--	--
Long Snap-in Latches								
		Order Code			Price Per Pack			
					1+	10+	50+	
Pack 20 (for 10 headers)		587-576 ●			342.00	291.00	276.00	

Male, Cable Mounted Header
Class II



- Cable mounted header with or without mounting lugs
- Headers are bump and click polarised (10 way is bump only).

208961

No. of Ways	Mftrs. List No.	Order Code	Price Each			
			1+	10+	50+	100+
Straight Pins - With Mounting Lugs						
10	4610-6050	525-091 ●	301.00	242.00	223.00	206.00
14	4614-6000	727-556 ●	255.00	204.00	189.00	174.00
16	4616-6000	727-568 ●	289.00	232.00	214.00	198.00
20	4620-6000	469-166 ●	397.00	319.00	295.00	256.00
26	4626-6000	469-178 ●	469.00	377.00	345.00	302.00
30	4630-6000	727-570 ●	456.00	407.00	376.00	326.00
34	4634-6000	469-180 ●	464.00	373.00	363.00	336.00
40	4640-6000	469-191 ●	550.00	442.00	404.00	376.00
50	4650-6000	469-208 ●	615.00	494.00	452.00	420.00
60	4660-6000	727-581 ●	738.00	593.00	577.00	534.00
64	4664-6000	727-593 ●	672.00	540.00	500.00	472.00
Straight Pins - Without Mounting Lugs						
10	4610-6051	413-9045 ●	478.00	384.00	351.00	307.00
14	4614-6001	413-9057 ●	583.00	469.00	429.00	399.00
16	4616-6001	413-9069 ●	586.00	471.00	431.00	377.00
20	4620-6001	413-9070 ●	561.00	451.00	412.00	361.00
26	4626-6001	413-9082 ●	689.00	554.00	506.00	443.00
34	4634-6001	413-9094 ●	689.00	588.00	545.00	512.00
40	4640-6001	413-9100 ●	735.00	590.00	547.00	485.00
50	4650-6001	413-9112 ●	774.00	661.00	613.00	576.00
64	4664-6001	413-9124 ●	882.00	733.00	698.00	656.00
Strain Relief Clips						
10	3448-4610	327-1353 ●	69.00	66.00	--	--
16	3448-4616	327-1377 ●	123.00	112.00	110.00	99.00
20	3448-4620	327-1389 ●	95.00	88.00	82.00	75.00
26	3448-4626	413-9150 ●	74.00	68.00	64.00	63.00
34	3448-4634	327-1419 ●	82.00	76.00	72.00	68.00
40	3448-4640	327-1420 ●	133.00	123.00	116.00	107.00
50	3448-4650	327-1432 ●	51.00	47.00	45.00	42.00
Ejectors						
Short	3505-16	413-9136 ●	17.00	14.00	14.00	12.00
Long	3505-17	413-9148 ●	17.00	14.00	13.00	11.00

'D' Tin and Dimple



- Delta 'D' connectors have a steel shell, provides screening continuity when correctly mounted
 - Contacts beryllium copper with gold plating
 - UL recognised and CSA approved
- Current rating 2A @ 70°C Housing Steel, tin Plating over copper
 Contact resistance 20mΩ max. Insulator Grey Polyester, **UL94V-0**
 Working voltage 350V ac/dc Contacts Formed, Beryllium Copper
 Temperature range -55°C to +125°C Plating (30μ") 0.76μ Gold over 1.27μ Nickel (Wiping area)
 Mating Cycles 200

208958

No. of Ways	Mftrs. List No.	Order Code	1+	10+	50+	100+	+
Plugs							
9	8209-8009	469-373 ●	579.00	465.00	425.00	396.00	--
15	8215-8009	469-385 ●	648.00	521.00	476.00	443.00	--
25	8225-8009	469-397 ●	718.00	577.00	528.00	491.00	--
37	8237-8009	469-403 ●	913.00	713.00	666.00	603.00	--
50	8250-6005	727-507 ●	1,520.00	1,188.00	1,180.00	1,130.00	--
Sockets							
9	8309-8009	469-415 ●	624.00	501.00	459.00	426	