

Switchgear Wire to BS6231 — Continued

25.0mm² (196/0.4mm) Type BK

Current rating **120A** at 35°C Nom. outside dia. 11

50m Reel

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	721-116	Red	721-153	Green/ Yellow	721-189

Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+

50m All Colours

35.0mm² (276/0.4mm) Type BK

Current rating **167A** at 35°C Nom. outside dia. 12.5

50m Reel

Colour	Order Code
Black	721-190


Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+

50m All Colours

Tri-Rated Control and Switchgear Wire



UL recognised, CSA certified and produced to **BS6231**. All cable is marked with the following:

AWG size, CSA TEW 105°C, UL1015 105°C, 600V, VW-1, BS6231 and conductor area in mm².

Max. operating temperature 105°C Voltage rating 600V rms ^{20X}

	16/0.2	24/0.2	32/0.2	30/0.25	50/0.25	56/0.3	84/0.3	80/0.4
Nominal outside dia. (mm)	2.6	2.8	3.0	3.3	3.8	4.3	5.0	6.8
Current rating @ 30°C (A)	10	13	18	22	31	41	53	75

0.5mm² (16/0.2mm) – 22 AWG

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	.584-988	Brown	.585-002	Red	.585-026
Blue	.584-990	Grey	.585-014	White	.585-038
				Green/ Yellow	.585-051

Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+ 25+

100m Plain & Bi-colour

0.75mm² (24/0.2mm) – 20 AWG

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	.585-063	Grey	.585-099	Violet	.585-129
Blue	.585-075	Orange	.585-105	White	.585-130
Brown	.585-087	Red	.585-117	Yellow	.585-142
				Green/ Yellow	.585-154

Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+ 25+

100m Plain & Bi-colour

1.0mm² (32/0.2mm) – 18 AWG

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	.585-166	Grey	.585-191	Violet	.585-221
Blue	.585-178	Orange	.585-208	White	.585-233
Brown	.585-180	Red	.585-210	Yellow	.585-245
				Green/ Yellow	.585-257

^{23X}

Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+ 25+

100m Plain & Bi-colour

1.5mm² (30/0.25mm) – 16 AWG

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	.585-269	Grey	.585-294	White	.585-324
Blue	.585-270	Orange	.585-300	Yellow	.585-336
Brown	.585-282	Red	.585-312	Green/ Yellow	.585-348

^{24X}

Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+ 25+

100m Plain & Bi-colour

2.5mm² (50/0.25mm) – 14 AWG

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	.585-350	Brown	.585-373	Yellow	.585-415
Blue	.585-361	Red	.585-397	Green/ Yellow	.585-427

^{25X}

Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+ 25+

100m Plain & Bi-colour

4.0mm² (56/0.3mm) – 12 AWG

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	.585-439	Brown	.585-452	Yellow	.585-488
Blue	.585-440	Red	.585-464	Green/ Yellow	.585-490

^{26X}

Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+ 25+

100m Plain & Bi-colour

6.0mm² (84/0.3mm) – 10 AWG

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	.585-506	Brown	.585-520	Yellow	.585-543
Blue	.585-518	Red	.585-531	Green/ Yellow	.585-555

^{27X}

Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+ 25+

100m Plain & Bi-colour

10mm² (80/0.4mm) – 8 AWG

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	.585-567	Red	.585-579	Green/ Yellow	.585-580

^{333X}

Price Per Reel

MIXED QUANTITY PRICING

1+ 5+ 10+ 25+

100m Plain & Bi-colour

Conduit Wire 6491B-LSF



Plain annealed copper conductors insulated in **LSF** (low smoke and fume) thermosetting insulation manufactured to **BS7211**.

Voltage rating 450/750V Max. operating temp. +90°C