

Heat Resisting Equipment Wire



Tinned stranded annealed copper conductors to **BS6360**. High temperature PVC insulated to **BS6746 Type 4**.

Max. continuous temperature	85°C (105°C for limited periods)			
	7/0.2	16/0.2	24/0.2	32/0.2
Nominal outside dia.	1.5	1.8	2.6	2.8
Nominal wall thickness	0.45	0.45	0.75	0.75
Voltage rating @ 20°C (V)	1000	1000	1200	1200
Current rating @ 20°C (A)	1.5	3.0	6.0	10.0

0.22mm² (7/0.2mm)

100m Reels	Colour	Order Code	Colour	Order Code
	Black	152-433	Red	152-435

Price Per Reel

MIXED QUANTITY PRICING

100m All Colours

1+	5+	10+	25+
----	----	-----	-----

0.5mm² (16/0.2mm)

100m Reels	Colour	Order Code
	Red	152-455

Price Per Reel

MIXED QUANTITY PRICING

100m All Colours

1+	5+	10+	25+
----	----	-----	-----

Tufsil 5000



- Silicone coated cable designed for use in the domestic appliance industry
- Silicone based insulation meets **BS6899** and **BS7655 E12** specifications
- Conductor meets **BS6360** specification
- **UL** approved

Maximum operating temperature	+180°C			Voltage rating	500Vdc & ac	
	24/0.2mm	7/0.4mm	30/0.25mm			
Nominal outside dia.	2.4	2.5	2.8			
Current rating	23A	25A	36A			



CAB649

Mftrs. List No.	Order Code	1+	5+	10+	25+
0.75mm² (24/0.2mm)					
25m White TSL24AW25	320-8758				
Red TSL24AR25	320-8760				
Black TSL24AB25	320-8771				
100m White TSL24AW100	320-8783				
Red TSL24AR100	320-8795				
Black TSL24AB100	320-8801				
1.0mm² (7/0.4mm)					
25m White TSL7CW25	320-8813				
Red TSL7CR25	320-8825				
Black TSL7CB25	320-8837				
100m White TSL7CW100	320-8849				
Red TSL7CR100	320-8850				
Black TSL7CB100	320-8862				
1.5mm² (30/0.25mm)					
25m White TSL30BW25	320-8874				
Red TSL30BR25	320-8886				
Black TSL30BB25	320-8898				
100m White TSL30BW100	320-8904				
Red TSL30BR100	320-8916				
Black TSL30BB100	320-8928				

PTFE Insulated Wire

Steel Wire Armoured Cable Glands



New

	No of Glands, Shrouds, Tags & Locknuts per Kit/Pack	Outer Sheath Min (mm)	Cable Dia Max (mm)
Indoor BWK Gland Packs			
20SBWK	2	12.9	15.8
20BWK	2	15.5	20.8
25BWK	2	20.3	27.2
32BWK	2	27.2	33.5
40BWK	1	33.5	40.5
50BWK	1	45.2	53.5
Outdoor CWK Gland Packs			
20SCWK	2	12.9	15.8
20CWK	2	15.5	20.8
25CWK	2	20.3	27.2

CAB637

Mftrs. List No.	Order Code	1+	5+	10+	25+	50+
20SBWK	725-7405					
20BWK	725-7417					
25BWK	725-7429					
32BWK	725-7430					
40BWK	725-7442					
50BWK	725-7454					
20SCWK	725-7466					
20CWK	725-7478					
25CWK	725-7480					

Silver Plated to BS3G210

Brand-Rex

New



- Silver plated solid and stranded copper conductors
- Insulated in PTFE to **BS3G210**
- Ideal for use where a high level of reliability is required
- Excellent resistance to oils and common acids
- Conforms to **Def Std 61-12 pt 8** (apart from Type A 28 and 26 AWG)

BS3G210 Type A 7/0.12mm (0.0859mm²) 28 AWG

Maximum outside dia.	0.73mm	Current rating	3A
Voltage rating	300V	Operating temperature	-50°C to +190°C (flexing environment) -75°C to +200°C (static environment)

25m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-0576	Red	322-0588	White	322-0590	Pink	322-0606
Blue	322-0618	Yellow	322-0620	Green	322-0631		

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-0643	Red	322-0655	White	322-0667	Pink	322-0679
Blue	322-0680	Yellow	322-0692	Green	322-0709		

	1+	5+	10+	25+
25m All Colours				
100m All Colours				

BS3G210 Type A 1/0.4mm (0.128mm²) 26 AWG

Maximum outside dia.	0.75mm	Current rating	4A
Voltage rating	300V	Operating temperature	-50°C to +190°C (flexing environment) -75°C to +200°C (static environment)

25m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-0710	Red	322-0722	White	322-0734	Pink	322-0746
Blue	322-0758	Yellow	322-0760	Green	322-0771		

100m Reels

Colour	Order Code	Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	322-0783	Red	322-0795	White	322-0801	Pink	322-0813
Blue	322-0825	Yellow	322-0837	Green	322-0849		

	1+	5+	10+	25+
25m All Colours				
100m All Colours				