

| Lead Length mm | Mfrs. List No. | Order Code | Price Each | | | |
|---|----------------|------------|------------|-----|-----|-----|
| | | | 1+ | 10+ | 25+ | 50+ |
| 0.5mm CSA Braid M3 – M3 | | | | | | |
| 100 | 1337666-1 | 353-2847 | | | | |
| 150 | 1337666-2 | 353-2859 | | | | |
| 200 | 1337666-3 | 353-2860 | | | | |
| 1.13mm CSA Braid M3.5 – M3.5 | | | | | | |
| 100 | 1337667-1 | 353-2872 | | | | |
| 150 | 1337667-2 | 353-2884 | | | | |
| 200 | 1337667-3 | 353-2896 | | | | |
| 2.26mm CSA Braid M8 – M8 | | | | | | |
| 100 | 1337668-1 | 353-2902 | | | | |
| 150 | 1337668-2 | 353-2914 | | | | |
| 200 | 1337668-3 | 353-2926 | | | | |
| 7.54mm CSA Braid M5 – M5 | | | | | | |
| 100 | 1337669-1 | 353-2938 | | | | |
| 150 | 1337669-2 | 353-2940 | | | | |
| 200 | 1337669-3 | 353-2951 | | | | |
| 8.29mm CSA Braid M5 – M5 | | | | | | |
| 100 | 1337670-1 | 353-2963 | | | | |
| 150 | 1337670-2 | 353-2975 | | | | |
| 200 | 1337670-3 | 353-2987 | | | | |
| 10mm CSA Braid M5 – M5 | | | | | | |
| 100 | 1337671-1 | 353-2999 | | | | |
| 150 | 1337671-2 | 353-3001 | | | | |
| 200 | 1337671-3 | 353-3013 | | | | |
| 15mm CSA Braid M6 – M6 | | | | | | |
| 150 | 1337706-1 | 353-3025 | | | | |
| 250 | 1337706-2 | 353-3037 | | | | |
| 400 | 1337706-3 | 353-3049 | | | | |
| 25mm CSA Braid M8 – M8 | | | | | | |
| 250 | 1337707-1 | 353-3050 | | | | |
| 400 | 1337707-2 | 353-3062 | | | | |
| 500 | 1337707-3 | 353-3074 | | | | |
| 0.5mm CSA Insulated Braid M3 – M3 | | | | | | |
| 100 | 1337708-1 | 353-3086 | | | | |
| 150 | 1337708-2 | 353-3098 | | | | |
| 200 | 1337708-3 | 353-3104 | | | | |
| 1.13mm CSA Insulated Braid M3.5 – M3.5 | | | | | | |
| 100 | 1337709-1 | 353-3116 | | | | |
| 150 | 1337709-2 | 353-3128 | | | | |
| 200 | 1337709-3 | 353-3130 | | | | |
| 2.26mm CSA Insulated Braid M8 – M8 | | | | | | |
| 100 | 1337710-1 | 353-3141 | | | | |
| 150 | 1337710-2 | 353-3153 | | | | |
| 200 | 1337710-3 | 353-3165 | | | | |
| 7.54mm CSA Insulated Braid M5 – M5 | | | | | | |
| 100 | 1337711-1 | 353-3177 | | | | |
| 150 | 1337711-2 | 353-3189 | | | | |
| 200 | 1337711-3 | 353-3190 | | | | |
| 8.29mm CSA Insulated Braid M5 – M5 | | | | | | |
| 100 | 1337712-1 | 353-3207 | | | | |
| 150 | 1337712-2 | 353-3219 | | | | |
| 200 | 1337712-3 | 353-3220 | | | | |

Automotive Wire



multicom
Best value
Automotive wire and cable plain conductors PVC insulated to **BS6862 Part 1**. Resistant to petrol, lubrication oils, fuel oils and dilute acids.

| | 14/0.3 | 21/0.3 | 28/0.3 |
|---------------------------|--------|--------|--------|
| Nominal outside dia. (mm) | 2.7 | 3.1 | 3.4 |
| Wall thickness (mm) | 0.6 | 0.6 | 0.6 |
| Current rating (A) | 8.75 | 13 | 17.5 |
| Test voltage | | | |
| Maximum temperature | | | |

1.0mm² (14/0.3)

| Colour | Order Code | Colour | Order Code |
|--------|------------|--------|------------|
| Black | 710-696 | Red | 710-775 |

| 500m All Colours | Price Per Reel | | | |
|------------------|-------------------------------|----|-----|-----|
| | 1+ | 5+ | 10+ | 25+ |
| | MIXED QUANTITY PRICING | | | |

1.5mm² (21/0.3)

| Colour | Order Code |
|--------|------------|
| Black | 710-817 |

| 500m All Colours | Price Per Reel | | |
|------------------|-------------------------------|----|-----|
| | 1+ | 5+ | 10+ |
| | MIXED QUANTITY PRICING | | |

2.0mm² (28/0.3)

| Colour | Order Code | Colour | Order Code |
|--------|------------|--------|------------|
| Black | 710-910 | Red | 710-982 |

| 500m All Colours | Price Per Reel | | |
|------------------|-------------------------------|----|-----|
| | 1+ | 5+ | 10+ |
| | MIXED QUANTITY PRICING | | |

9/0.3 Twin Flat

Two cores laid together and sheathed in Black PVC forming an oval cable.

| | | | |
|----------------|---------------|----------------------|---------|
| Core colours | Red and Black | Nominal dimensions | 3.8 6.1 |
| Current rating | 5.75A | Max. operating temp. | +70°C |

| 100m Flat Twin | Price Per Reel | | |
|----------------|-------------------------------|----|-----|
| | 1+ | 5+ | 10+ |
| | MIXED QUANTITY PRICING | | |

Seven Core Trailer Cable




| | | |
|---------|--|-------|
| Central | White (2.0mm ²) | 17.5A |
| Outer | Brown, Blue, Black Yellow, Red and Green (1.0mm ²) | 8.75A |

| | |
|-----------------------|------|
| Maximum overall dia. | 10.2 |
| Wall thickness sheath | 0.8 |
| Wall thickness cores | 0.6 |

423

| 100m 7-Core | Price Per Reel | | |
|-------------|-------------------------------|----|-----|
| | 1+ | 5+ | 10+ |
| | MIXED QUANTITY PRICING | | |

Welding Cables



- Plain copper conductors sheathed in black chlorinated neoprene
- Manufactured to **HOIN-2D**.

| Size (mm ²) | 100% | Current Rating (A) | | Temperature rating | -20°C to +80°C |
|-------------------------|------|--------------------|-----|--------------------|----------------|
| | | 60% | 30% | | |
| 16 | 135 | 175 | 245 | 11.5 | 313-8495 |
| 25 | 180 | 230 | 330 | 13.0 | 313-8501 |
| 35 | 225 | 290 | 410 | 14.5 | 313-8513 |

Ambient air temperature 25°C, maximum conductor temperature 85°C.

* Duty cycle is the time for which the current flows.

The above figures are based on a percentage of the complete cycle, taken as 5 minutes.

387X

| 50m Reel | Price Per Reel | | |
|-------------------|----------------|----|-----|
| | 1+ | 5+ | 10+ |
| 16mm ² | 313-8495 | | |
| 25mm ² | 313-8501 | | |
| 35mm ² | 313-8513 | | |

Major International Brands

All the leading brand names from over 1,000 major international manufacturers.