

## Mains Flex - 2-Core — Continued

### 2182Y – Round 300/500V

Conductor Area (mm <sup>2</sup> )	Construction	Current Rating	Nominal Dia.	Harmonised Code
0.5	16/0.2	3A	5.4	H03VV-F2
0.75	24/0.2	6A	5.8	H03VV-F2

BS6500 Table 15

### 16/0.2 (0.5mm<sup>2</sup>) 3A

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	721-360	Grey	721-372	White	721-384

### 24/0.2 (0.75mm<sup>2</sup>) 6A

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	721-396	Grey	721-402	White	721-414

416X

#### Price Per Reel

100m Reels	1+	5+	10+	25+	50+
3A All Colours					
6A All Colours					

### 3182Y – Round 300/500V

Conductor Area (mm <sup>2</sup> )	Construction	Current Rating	Nominal Dia.	Harmonised Code
0.5	16/0.2	3A	6.3	—
0.75	24/0.2	6A	6.8	H05VV-F2
1.0	32/0.2	10A	7.2	H05VV-F2
1.25	40/0.2	13A	7.8	—
1.5	30/0.25	15A	8.2	H05VV-F2
2.5	50/0.25	20A	10.0	H05VV-F2

BS6500 Table 16

3A	Colour	Order Code	Colour	Order Code	Colour	Order Code
	Black	721-426	Grey	721-438	White	721-440

6A	Colour	Order Code	Colour	Order Code
	Black	.721-451	White	.721-475
	Grey	.721-463	Orange	.721-487

10A	Colour	Order Code	Colour	Order Code	Colour	Order Code
	Black	721-499	Grey	721-505	White	721-517

13A	Colour	Order Code
	Black	721-529

15A	Colour	Order Code	Colour	Order Code
	Black	721-530	White	721-554

20A	Colour	Order Code
	Black	721-566


417X

#### Price Per Reel

100m Reels	1+	5+	10+	25+	50+
3A All Colours					
6A All Colours					
10A All Colours					
13A All Colours					
15A All Colours					
20A All Colours					

## Mains Flex - 3-Core

multicomp



- PVC insulated and sheathed flexible mains cords
- Manufactured to BS6500

Best value

### 2183Y – Round 300/300V

Conductor Area (mm <sup>2</sup> )	Construction	Current Rating	Nominal Dia.	Harmonised Code
0.5	16/0.2	3A	5.6	H03VV-F3
0.75	24/0.2	6A	6.1	H03VV-F3

BS6500 Table 15

### 16/0.2 (0.5mm<sup>2</sup>) 3A

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	721-578	Grey	721-580	White	721-591

### 24/0.2 (0.75mm<sup>2</sup>) 6A

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	721-608	Grey	721-610	White	721-621

418X

#### Price Per Reel

100m Reels	1+	5+	10+	25+	50+
3A All Colours					
6A All Colours					

### 3183Y – Round 300/500V

Conductor Area (mm <sup>2</sup> )	Construction	Current Rating	Nominal Dia.	Harmonised Code
0.75	24/0.2	6A	6.8	H05VV-F3
1.0	32/0.2	10A	7.2	H05VV-F3
1.25	40/0.2	13A	7.8	—
1.5	30/0.25	15A	8.2	H05VV-F3
2.5	50/0.25	20A	10.0	H05VV-F3

BS6500 Table 16

### 24/0.2 (0.75mm<sup>2</sup>) 6A

Colour	Order Code	Colour	Order Code
Black	.721-633	White	.721-669
Grey	.721-645	Orange	721-670

### 32/0.2 (1.0mm<sup>2</sup>) 10A

Colour	Order Code	Colour	Order Code
Black	.721-682	Grey	.721-694
White	721-700	Orange	.436-732

### 40/0.2 (1.25mm<sup>2</sup>) 13A

Colour	Order Code	Colour	Order Code
Black	721-712	White	.721-736
Grey	721-724	Orange	.721-748

### 30/0.25 (1.5mm<sup>2</sup>) 15A

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	721-750	Grey	721-761	White	721-773

### 50/0.25 (2.5mm<sup>2</sup>) 20A

Colour	Order Code	Colour	Order Code	Colour	Order Code
Black	721-785	White	721-797	Orange, 50m	277-400

### 56/0.30 (4.0mm<sup>2</sup>) 25A

Colour	Order Code	Colour	Order Code
Black, 50m	267-351	White, 50m	267-363


419X

#### Price Per Reel

100m Reels	1+	5+	10+	25+	50+
6A All Colours					
10A All Colours					
13A All Colours					
15A All Colours					
20A Black, White					
20A Orange 50m Reel					
25A All Colours, 50m Reel					

## Coiled Mains Flex (0.20, 0.75 and 1.25mm<sup>2</sup>)

multicomp



- Three core, Blue, Brown and Green/Yellow
- PVC insulated extendable mains lead available in three current ratings
- Moulded into a coiled Black or White PVC sheath.

Conductor Area	Length Closed	Length Extended	Current Rating
0.2mm <sup>2</sup>	0.23m	1.50m	1A
0.75mm <sup>2</sup>	0.50m	2.44m	6A
1.25mm <sup>2</sup>	0.50m	2.36m	13A

45X

Conductor Area	Order Code	Price Each			
		1+	25+	50+	100+
<b>Black</b>					
0.2mm <sup>2</sup>	151-202				
0.75mm <sup>2</sup>	151-204				
1.25mm <sup>2</sup>	151-206				
<b>White</b>					
0.2mm <sup>2</sup>	.151-203				
0.75mm <sup>2</sup>	.151-205				
1.25mm <sup>2</sup>	.151-207				

## Mains Flex - 4 & 5-Core

### 0.75, 1.0, 1.5 and 2.5mm<sup>2</sup> – 3184Y/3185Y

multicomp



- 4 and 5 core PVC insulated copper conductors. Sheathed overall in Black PVC to BS6500 Table 16, harmonised code H05VV-F. 4 core brown, blue, black, green/yellow. 5 core as above +1 black conductor

Voltage rating 300/500V

Price Reduced