

## Phono Colour Coding Rings To Fit Line Plugs and Sockets



- Provide easy cable identification
- Fit between connector and backshell
- Multicolour or stereo pack options
- For use with connectors, Order Codes 260-915 to 260-976, 430-249 to 430-274.

CA062

	Order Code	Price Per Pack		
		1+	5+	10+
<b>60 Per Pack</b>				
<b>Multicolour Pack</b>				
12 black, 12 red, 10 yellow, 10 blue, 10 green, 3 brown, 3 white	<b>149-270</b>			
<b>Stereo Pack</b>				
30 black, 30 red	<b>149-271</b>			

## Colour Coded Anodised Housings



L = 60.5, (45 excl. spring),  
Dia. = 10.8 Cable entry = 5.5 max.

- Colour coded housings
- Gold plated brass contacts
- Solid centre pin
- Large solder bucket
- PTFE insulator
- Large cable entry
- Pre-formed cable clamp
- Patented 'T'-slot ground contact

Current rating	5A @ 200V dc/150V ac max.	Insulator	PTFE
Insulation resistance	100MΩ @ 500V dc	Contacts	Brass, flash gold plated
Housing	Aluminium, anodised colour coded		
Strain relief spring	Black chrome		

Body Colour	Mftrs. List No.	Order Code	Price Each			
			1+	50+	100+	250+ 500+
Black	346-0100	<b>430-249</b>				
Blue	346-0200	<b>430-250</b>				
Red	346-0500	<b>430-262</b>				
Yellow	346-0700	<b>430-274</b>				

## Studio Grade



L = 36 max., Dia. = 12 Cable entry = 6 max.

- 5 piece part construction
- Solid centre pin
- Machined brass
- Fully shrouded ground
- P.T.F.E. insulator contact
- Gold plated contacts
- Collet type cable
- Satin nickel body finish clamp & ground contact

CA064

Colour Code	Order Code	1+	16+	48+	100+
Black	<b>745-364</b>				
Red	<b>745-376</b>				

## High End Shrouded Ground Plugs



L = 62.6, (46.3 excl. spring), Dia. = 12.4, Cable entry = 5.5 max.

- Machined brass construction
- 0.5 micron gold plated contacts
- Solid centre pin
- Large solder bucket
- PTFE insulator
- Fully shrouded ground contact
- Maximum RFI/EMI shielding
- Gold or black chrome options
- Large cable entry
- Patented 'T'-slot ground contact

Current rating	5A @ 200V dc/150V ac max.	Strain relief springs	Black chrome or flash gold plated
Insulation resistance	100MΩ @ 500V dc	Insulator	PTFE
Housing	Brass, black chrome or flash gold plated, red/white colour coding	Contacts	Brass, 0.5µ gold plated

CA065

Colour Code	Mftrs. List No.	Order Code	1+	25+	50+	100+	250+
<b>Flash Gold Cap/Spring</b>							
Red	320-0500	<b>430-286</b>					
White	320-0600	<b>430-298</b>					
<b>Black Chrome Cap/Spring</b>							
Red	321-0500	<b>430-304</b>					
White	321-0600	<b>430-316</b>					

## Through Ground Collet Plug 0.5 Micron, Black Chrome Cap



L = 54, Dia. = 12, Cable entry = 6.0 max.


- Machined brass construction
- Dual grounding cable clamp collet
- 0.5 micron gold plated contacts
- Solid centre pin
- Large solder bucket
- PTFE insulator
- Large cable entry
- Digital signal capability
- Patented 'T'-slot ground contact

Current rating	5A @ 200V dc/150V ac max	Insulator	PTFE
Insulation resistance	100MΩ @ 500V dc	Contacts	Solid brass, 0.5µ gold plated
Housing	Brass, black chrome red/white colour coded		

CA066

Body/Colour Code	Mftrs. List No.	Order Code	Price Each				
			1+	10+	25+	50+	100+
Black/Red	345-0500	<b>430-225</b>					
Black/White	345-0600	<b>430-237</b>					

## 'Profi' Plugs



L = 54 max, Dia = 13, Cable entry = 3.0-7.3

- Gold plated contacts
- Spring loaded earth contact
- Makes ground before signal
- Breaks signal before ground
- Prevents possible noise damage
- Chuck type strain relief
- Two strain relief size options
- Wide cable entry range
- Matt black finish, colour coded
- Supplied as pair with strain reliefs

Current rating	16A max	Housing	Brass, Cu alloy
Rated voltage	250V ac	Insulator	Polyester PBTP
Proof voltage	1500V ac	Contacts	Pin Brass, Cu alloy gold plated
Insulation resistance	1.1GΩ	Earth	Bronze, nickel and 0.5µ gold plated

Mftrs. List No. NF2C2B

CA067

2 Per Pack	Order Code	Price Per Pair			
		1+	25+	50+	100+ 250+
Red and Black	<b>.250-739</b>				

## Elbow M/F and 'T' M/F/F Colour Coded Red and Black



Elbows L = 33 (plug - rear), L = 24.5 (socket - rear), W = 12.8 'T' Adaptors L = 55 (plug - socket), 'T' L = 25, W = 12.8

- Gold plated contacts for improved conductivity
- Bodies overmoulded in colour coded PVC



CA068

Elbow	Order Code	Price Each			
		1+	4+	8+	24+ 48+ 100+
Red	<b>779-337</b>				
Black	<b>779-325</b>				
<b>T' Adaptor</b>					
Red	<b>779-301</b>				
Adaptor	<b>779-313</b>				

continued