



## 4mm Stackable Plugs 30A

MC



A range of 4mm stackable plugs offering multi-way stacking in any of three 4mm sockets provided. This unique flexibility allows patch leads to be joined together or bunched as shown above



Current rating	32A	Housing	Polypropylene, <b>UL94-HB</b>
Operating voltage	30V ac/60V dc	Contacts	Beryllium copper, nickel plated
Temperature range	-40°C to +75°C	Termination	Solder

Mfrs. List No. L471+Colour

CS185

Colour	Order Code	Colour	Order Code	Colour	Order Code
Red	<b>143-882</b>	Green	<b>143-883</b>	Yellow	<b>143-885</b>
Black	<b>143-881</b>	Blue	<b>143-884</b>		
		<b>Price Each</b>			
<b>Order Code</b>	1+	50+	100+	250+	500+
All colours					

## 4mm Cage Clamp Plugs 20A



H = 15, W = 8, L = 40  
Push to insert/release wire  
Cage clamp mechanism

The spring cage clamp is vibration proof, reliable and fast to operate. Simply strip the insulation back to 10mm and insert the wire by pressing the housing together fully. The cage clamp can accept either stranded or solid wire yet still have the same retaining force as a standard screw terminal.

Current rating	20A	Housing	Nylon 6.6
Operating voltage	380Vac (Group B)	Contacts	Copper, tin/lead plated
Contact resistance	1.2mΩ	Temp. range	-40°C to +105°C
Test voltage	2500V		


Mfrs. List No. 215-212 = 258-039, 215-311 = 258-040, 215-411 = 258-052

CS225

5 Per Pack	Price Per Pack					
Colour	Order Code	1+	10+	20+	50+	100+
Red	<b>258-039</b>					
Black	<b>258-040</b>					
Green	<b>258-052</b>					

## 4mm Plugs 16A

Best value



4mm plug L = 51  
Plug with 4mm transverse hole L = 59.5



Fully mating universal plugs with shatter-proof insulating sleeve. The sleeve narrows at the end to prevent cable buckling. Available with or without 4mm transverse hole and screw terminations.

Operating voltage	50V	Temperature range	-25°C to +70°C
Continuous load current	16A	Housing	PVC
Contact resistance	3mΩ	Contacts	Brass, nickel plated

Mfrs. List No. VON 20+Colour, no hole, Screw-terminal  
VON30+Colour, no hole, Solder-terminal,  
VQ20+colour, transverse hole, Screw-terminal,  
VQ30+colour, transverse hole, Solder-terminal

CS293

### 5 Per Pack

Order Code	Price Per Pack				
	1+	10+	25+	50+	100+
<b>4mm Plug, Screw Terminal</b>					
Red	<b>497-617</b>				
Black	<b>497-629</b>				
Blue	<b>809-949</b>				
Yellow	<b>400-2799</b>				
Green	<b>400-2805</b>				
Red, Black, Blue, Yellow, Green	<b>497-642</b>				
<b>4mm Plug, Solder</b>					
Red	<b>809-962</b>				
Black	<b>809-950</b>				
Blue	<b>809-974</b>				
Yellow	<b>400-2817</b>				
Green	<b>400-2829</b>				
<b>4mm Plug with Transverse Hole</b>					
Red	<b>497-666</b>				
Black	<b>497-678</b>				
Blue	<b>810-046</b>				
Yellow	<b>400-2830</b>				
Green	<b>400-2842</b>				
Red, Black, Blue, Yellow, Green	<b>497-691</b>				
<b>4mm Plug, Transverse Hole, Solder</b>					
Red	<b>810-060</b>				
Black	<b>810-058</b>				
Blue	<b>810-071</b>				
Yellow	<b>400-2854</b>				
Green	<b>400-2866</b>				

## 4mm Plugs 32A



- Laminated shatter-proof plug
- Caged spring and tapering sleeve
- Soldered connections up to 2.5sqmm<sup>2</sup>
- Cable diameters up to 4.2mm<sup>2</sup>



Rated voltage	60Vdc	Contact resistance	3mΩ
Current rating	32A	Temperature range	-25°C to 70°C


Mfrs. List No. 972518-100 (black), 9725178-101 (red)

CS546

### 5 Per Pack

Colour	Order Code	Price Per Pack				
		1+	10+	25+	50+	100+
Red	<b>401-7470</b>					
Black	<b>401-7481</b>					

## 4mm Bunch Pin Plugs 16A



Multiple-spring wire plug with shatter-proof flexible insulating sleeve and transverse 4mm hole. The sleeve narrows to prevent cable buckling. Solder or screw connection up to max. cross-section 1.5mm<sup>2</sup>



L = 60.5, Dia. = 11	Operating voltage	50V	Temperature range	-25°C to +70°C
	Continuous load current	16A	Housing	PVC
	Contact resistance	3mΩ	Material	Brass, nickel plated

Mfrs. List No. BULA 20K + colour (screw), BULA 30K + colour (solder)

CS292

### 5 Per Pack

Order Code	Price Per Pack				
	1+	10+	25+	50+	100+
<b>Screw Termination</b>					
Red	<b>495-645</b>				
Black	<b>495-657</b>				
Blue	<b>810-083</b>				
Yellow	<b>400-2878</b>				
Green	<b>400-2880</b>				
Red, Black, Blue, Yellow, Green	<b>495-682</b>				
<b>Solder Termination</b>					
Red	<b>495-700</b>				
Black	<b>495-712</b>				
Blue	<b>810-095</b>				
Yellow	<b>400-2891</b>				
Green	<b>400-2908</b>				
Red, Black, Blue, Yellow, Green	<b>495-736</b>				

continued