

DIN Rail Terminals — continued

Fuse Disconnect Terminals




- Only 60mm wide across the DIN rail
- Range includes metric and imperial fuse sizes
- Cage Clamp which guarantees gas tight connection of conductors up to 4mm²
- Each fuseholder has storage for a spare fuse
- Rated Voltage 800V/8kV/3

Fuse Size	Conductor Size	Current	Dimensions			Colour
			W	L	H	
5 20mm	4mm ²	10A Slow Acting, 6.3A Fast Acting	8	60	60	Grey
5 25mm	4mm ²	10A Slow Acting, 6.3A Fast Acting	8	60	60	Grey
1 ¼ 1 ¼"	4mm ²	10A Slow Acting, 6.3A Fast Acting	8	60	60	Grey

CTL310

Mftrs List No.	Fuse Size	Order Code	Price Each		
			1+	10+	50+
281-611	5 20mm fuse	319-0195			
281-612	5 25mm fuse	319-0201			
281-623	¼ ¼"	319-0213			
281-311	Endplate	319-0225			

Mini Blade Type (Car) Fuse Terminals Angle Entry



- Use the popular blade type fuses as used in many vehicles
- Angle entry of conductor saves space
- Each Cage Clamp has a test point
- Designed for conductors up to 6mm²
- Rated Voltage 400V/6kV/3

Mftrs List No.	Current	Conductor Size	Dimensions			Colour
			W	L	H	
282-696	30A	6mm ²	8	85	38.5*	Grey
282-334	-	-	2mm thick			Grey

* including fuse

CTL311

Mftrs List No.	Order Code	Price Each		
		1+	10+	50+
282-696	Fuse Terminal	319-0237		
282-334	Endplate	319-0249		

CT & VT Disconnect / Test Terminals



- Suitable for solid, stranded and flexible conductors
- Cage Clamp guarantees gas tight connection
- Touchproof test plug, 4mm diameter
- Disconnect link on disconnect/test terminals

Colour	Insulation group	Current	Width	Conductor Size
Grey	500V/6kV/3	30A	8mm	6mm ²

Mftrs List No.	Order Code	Mftrs List No.	Order Code
282-870	321-5222	282-860	321-5246
282-865	321-5234	282-866	321-5258

CTL321

Description	Circuits	Link Colour	Price Each		
			Order Code	1+	10+
Disconnect/test terminal	CT	Orange	321-5222		
Through terminal	CT	-	321-5234		
Disconnect/test terminal	VT	Light Grey	321-5246		
Through terminal	VT	-	321-5258		

CT & VT Disconnect / Test Terminal Accessories



- Lock out prevents accidental operation of the disconnect link
- Locking cover locks together several links and protects markers
- Interlocking link groups together several links

Mftrs List No.	Description	Colour	For use with terminal type	Width
282-386	End & Intermediate Plate, for use without lock out seal	Orange	Disconnect/Test terminal	1.5mm
282-391	End & Intermediate Plate, for use without lock out seal	Grey	Disconnect/Test terminal	1.5mm
282-387	End & Intermediate Plate, for use with lock out seal	Orange	Disconnect/Test terminal	1.5mm
282-392	End & Intermediate Plate, for use with lock out seal	Grey	Disconnect/Test terminal	1.5mm
282-385	End & Intermediate Plate	Orange	Through terminal	1.5mm
282-390	End & Intermediate Plate	Grey	Through terminal	1.5mm

CTL322

Mftrs List No.	Description	Colour	Order Code	Price Each		
				1+	10+	50+
282-386	End & Intermediate Plate	Orange	321-5260			
282-391	End & Intermediate Plate	Grey	321-5271			
282-387	End & Intermediate Plate	Orange	321-5283			
282-392	End & Intermediate Plate	Grey	321-5295			
282-385	End & Intermediate Plate	Orange	321-5301			
282-390	End & Intermediate Plate	Grey	321-5313			
282-384	Lock Out	Yellow	321-5325			
282-881	Locking Cover, 1 pole	Transparent	321-5337			
282-882	Locking Cover, 2 pole	Transparent	321-5349			
282-883	Locking Cover, 3 pole	Transparent	321-5350			
282-884	Locking Cover, 4 pole	Transparent	321-5362			
210-254	Interlocking Link, 1m long	Transparent	321-5374			
282-402	Adjacent Jumper	Grey	321-5386			
282-424	Adjacent Jumper	Orange	321-5398			

DIN Rail Enclosure Optional PCB




- Universal Mounting (TS35 or TS32)
- Available in 4 sizes
- Complete with screw terminals
- Moulded from Grey Polyamide 6.6

Rated at 10A 250V
Max Cable Size 4mm²

CTL326

Type	H	W	D	Terminal	Order Code	Price Each		
						1+	10+	50+
1	63	20	58	4	318-7834			
2	90.5	16.5	58	4	318-7846			
3	90.5	22.5	58	6	318-7858			
4	90.5	28.5	58	8	318-7860			
PCB for type 1					318-7871			
PCB for type 2, 3 & 4					318-7883			

Double Deck Earth Terminal Block



- Ground earth conductor/ through terminal blocks
- Rated voltage 500V/6kV/3

Wire Size: 0.08mm² - 2.5mm²
Width: 5mm
Rated Current: 20A
Insulation Strip Length: 8-9mm
Colour: green-yellow/grey

din044

Mftrs List No.	Order Code	Price Each		
		1+	10+	50+
280-527	805-166			

Double Deck Terminal Block



- Through/through terminal blocks
- With horizontal jumpering on lower level
- Front entry
- Rated voltage 500V/6kV/3

Mftrs List No.	Colour	Width (mm)	Rated Current	Wire Size (mm ²)	Suitable end Plate
280-520	Grey/grey	5	20A	0.08-2.5	805-191
281-620	Grey/grey	6	26A	0.08-4.0	805-324

din045