

Operator Interfaces — continued

Operating Interface
PMU300



IMO

New

3 YEAR
GUARANTEE

Ideal for replacing conventional panel designs using lamps, mimics and pushbuttons.

Features include:-

- Mono black and white or mono blue LCD options
- 320 240 pixel 5.7" graphic display
- Touch screen display
- 256k flash EPROM memory
- 16 programmable function keys
- 4 inputs, 11 outputs
- 24V dc supply
- Drivers for IMO PLCs plus other manufacturers
- PMU screen configuration software provided

PMU-300BT-FAR	327-8918	PMO-300S-FAR	327-8931
PMU-300LT-FAR	327-8920		

inc278

	Order Code	1+	5+	10+	25+
Blue LCD	327-8918				
Black & White LCD	327-8920				
RS232/RS485 Serial Interface	327-8931				

Operator Interface
PMU600



IMO

New

3 YEAR
GUARANTEE

Ideal for replacing conventional panel designs using lamps, mimics and pushbuttons.

Features include:-

- EL-mono, EL-Colour and TFT-LCD 16 colour
- 640 480 pixels (VGA) 10.4 inch display
- Touch screen display
- 512k flash EPROM memory

- 12 programmable function keys
- 4 inputs, 11 outputs
- Printer port
- 110/240 Vac supply
- PMU screen configuration software provided

PMU-600TT-FAR	327-8943	PMU-600ET-FAR	327-8967
PMU-600CT-FAR	327-8955	PMO-600S	327-8979

inc278

	Order Code	1+	5+	10+	25+
TFT 16 Colour	327-8943				
Luminescence 8 Colour	327-8955				
Luminescence Mono	327-8967				
RS232/RS485 Serial Interface	327-8979				

Operator Interface Terminals



PARADIGM

- Compatible with most PLCs
- Over 60 serial communications protocols
- Full dial-in/dial-out modem support
- Powerful 500 pint alarm scanner
- Comprehensive real time trending package
- Terminals can be networked for factory wide data collection

Displays are backlit LCD all units have RS232 and RS485 ports and are sealed to IP65 from the front panel

Display Size (Pixels)	2 20	2 40	2 20
H	162	106	66
L	206	285	206
D	66	106	66
Soft Keys	3	5	3
Function Keys	8	-	8
Numeric Keyboard	yes	no	yes
Real-Time Clock	yes	yes	yes
Power Supply	24V dc	24V dc	24V dc
Mfrs. List No.	CL10	CL15	CL20
Order Code	711-0789	711-0790	711-0807

Mfrs. List No.	Order Code	1+	5+	10+	15+	20+
CL10	711-0789					
CL15	711-0790					
CL20	711-0807					

inc64

Operator Interface Terminals



PARADIGM

- Compatible with most PLCs
- Over 60 serial communications protocols
- Full dial-in/dial-out modem support
- Powerful 500 pint alarm scanner
- Comprehensive trending package
- Terminals can be networked for factory wide data collection

Displays are CCFL liquid crystal. Both units have RS232 and RS485 ports and are sealed to IP65 from the front panel

Display Size (Pixels)	2 56 128	2 56 128
H	162	199
L	206	224
D	67	67
Soft Keys	4	4
Function Keys	-	12
Numeric Keyboard	no	yes
Real-Time Clock	yes	yes
Power Supply	10-40V dc	24V ac
Mfrs. List No.	GL300	GL350
Order Code	711-2117	711-2129

inc65

Mfrs. List No.	Order Code	1+	5+	10+	15+	20+
GL300	711-2117					
GL350	711-2129					

Operator Terminal Software and Converter PARADIGM



- Powerful and easy-to-use package
- Offers: trending, 500 point alarm scanner, networking, real time analysis and event logging
- Includes a comprehensive reporting feature
- Comes with program cable and a comprehensive manual
- Communications converter in convenient DIN rail package for simple conversion from RS232 to RS485


inc66

Mfrs. List No.	Order Code	1+	5+	10+	15+	20+
Converter PDCM000	711-8260					
Software PDSF0000	711-2294					

Fieldbus

Flex I/O System
Flex I/O I/O Modules

Rockwell Automation



Flex I/O Digital Modules

New

Inputs: DC 10-30V dc rated
Outputs: Relay Volt free 2A @ 5-265V ac, 2A @ 24V dc
DC Transistor 20.4 - 26.4V dc, 0.5A

A-B Part Number	Input Type	No. Inputs	No. Outputs	Order Code
1794-IB16	DC	16	-	351-5928
1794-OB16	DC	-	16	351-5930
1794-OW8	DC	-	8 relay	351-5941

Flex I/O Analogue Modules

Module Type	Specification
Input	0-10V, +/-10V, 0-20ma, 4-20ma, 12 bit resolution (11 bit bipolar)
	Single ended inputs
Output	0-10V, +/-10V, 0-20ma, 4-20ma, 12 bit resolution
	Single ended Outputs

A-B Part Number	No. Inputs	No. Outputs	Order Code
1794-IE8	8	-	351-5953
1794-OE4	-	4	351-5965