

Feature	Specification
<b>Mechanical:</b>	
Body	ABS 94V0
Dimensions	60H x 65W x 210L mm
Weight	1.5Kg
Interconnection	RS232 cable, RJ45 -> DB9F, 5 feet
<b>Environment:</b>	
Operation	-10 to 60 degree Celsius 10 to 80% humidity, non condensing
Storage	-20 to 70 degree Celsius 10 to 90% humidity, non condensing

OC553

Order Code	Price Each
<b>309-7043</b>	1+

Optional I/F cables for 1023 MSR, 1045 Fixed CCD Scanner & Tiny Decoders



OC563

Description	Order Code	Price Each		
		1+	5+	10+
1.2M straight cable, DIN5 for PCAT .....	<b>309-6956</b>			
1.2M straight cable, Mini-DIN6 for PS2, PS55, PCAT .....	<b>309-6968</b>			
1.2M straight cable, Mini-DIN6 for Macintosh.....	<b>309-6970</b>			
1.2M straight cable, Female DB9 for RS232 single port operation.....	<b>309-6981</b>			
1.2M straight cable, DB25 connectors for RS232 dual port operation for terminals	<b>309-6993</b>			
1.2M straight cable, Phonejack 10P10C for Aux RS232 port on Tiny III, DB9 Female connector for RS232 interface	<b>309-7006</b>			
1.2M straight cable, Phonejack 10P10C for Aux RS232 port on Tiny III, DB9 Female connector for RS232 input device.....	<b>309-7018</b>			
1.2M straight cable, two Phonejack 10P10C connectors, for Tiny III cloning transmission.....	<b>309-7020</b>			
1.2M straight cable, Phonejack 10P10C connector and DB15 male connector, for Tiny III networking .....	<b>309-7031</b>			

## Free Same Day Delivery

For orders received before 12.30pm we provide free same day delivery.