

## Dichroic-GU5.3/GX5.3



**GU5.3**  
 H = 22.2 (inc. clip), W = 19.2, D = 17  
 2 mtg holes Dia 3.6 @ 12 ctrs  
 Lead Length = 140

**GX5.3**  
 H = 16.8, W = 18.6, D = 10.3  
 2 mtg holes Dia 4 @ 12 ctrs  
 Lead Length = 160

**Best Value**

Low voltage dichroic lamp holders designed to accommodate GU5.3 and GX5.3 style lamps. Max voltage 50V.

SEC233X

Order Multiple=5		Price Each		
Type	Order Code	5+	50+	250+
GU5.3	<b>.530-669</b>			
GX5.3	<b>258-908</b>			

## Fluorescent Tubes

### T5 PLUS High Efficacy Fluorescent Tubes



- Superior colour rendering from T5 tubes
  - New generation of high efficacy tubes
  - Includes triphosphor technology for superior lumen maintenance
- OSRAM**  
**New**

Wattage	Length mm	Colour	Order Code
14W	549	warm white	317-8857
14W	549	cool white	317-8869
21W	849	warm white	317-8870
21W	849	cool white	317-8882
28W	1149	warm white	317-8894
28W	1149	cool white	317-8900
35W	1449	warm white	317-8912
35W	1449	cool white	317-8924

SEC103

**10 Per Pack**

Mftrs. List No.	Order Code	Price Each	
		10+	50+
FH1483	<b>317-8857</b>		
FH1484	<b>317-8869</b>		
FH2183	<b>317-8870</b>		
FH2184	<b>317-8882</b>		
FH2883	<b>317-8894</b>		
FH2884	<b>317-8900</b>		
FH3583	<b>317-8912</b>		
FH3584	<b>317-8924</b>		

### T8 Lumilux Plus ECO Fluorescent Tubes



- Reduced mercury content over other tubes
  - Exceptionally high lumen output
  - High efficacy with good colour rendering
  - Use with Osram Quicktronic Professional Electronic control gear
  - Available in three colour temperatures
- OSRAM**  
**New**

Wattage	Length	Colour	Order Code
18W	2'	warm white	317-7270
18W	2'	cool white	317-7282
18W	2'	white	317-7294
36W	4'	warm white	317-7300
36W	4'	cool white	317-7312
36W	4'	white	317-7324
58W	5'	warm white	317-7336
58W	5'	cool white	317-7348
58W	5'	white	317-7350
70W	6'	warm white	317-7361
70W	6'	cool white	317-7373
70W	6'	white	317-7385

SEC102

### 10 Per Pack

Mftrs. List No.	Order Code	Price Each	
		10+	50+
L18830	<b>317-7270</b>		
L18840	<b>317-7282</b>		
L18835	<b>317-7294</b>		
L36830	<b>317-7300</b>		
L36840	<b>317-7312</b>		
L36835	<b>317-7324</b>		
L58830	<b>317-7336</b>		
L58840	<b>317-7348</b>		
L58835	<b>317-7350</b>		
L70830	<b>317-7361</b>		
L70840	<b>317-7373</b>		
L70835	<b>317-7385</b>		

## Suspended Fluorescent 'Merlin'

## WHITECROFT LIGHTING

- High quality and stylish suspended fluorescent
- Suitable for offices, walkways, hotels, museums etc, LG3 1996 & cat 2.2 compliant
- All main body components in high quality low weight extruded aluminium
- 70% light down, 30% light up
- Includes energy efficient high frequency control gear
- Lamp order codes 3178912 (warm white), 3178924 (cool white)

**New**

Standard	Mftrs. List No.	Height	Length	Width	Order Code
Emergency	275/MER/S	65	1522	280	3533499
	275/MER/S/EMIN	65	1522	280	3533505

SEC532

		Price Each		
Order Code		1+	5+	10+
<b>353-3499</b>				
<b>353-3505</b>				

## Control Gear

### Quicktronic for High Efficacy T5 Lamps Single and Twin Operation

## OSRAM



- Modern electronic high frequency control gear in linear format for the new generation of slimline lighting systems using the new high efficacy FHT5 fluorescent tubes
- Constant power output to the tubes
- Efficient pre-heat start within 2 secs.
- Flicker free start and operation
- Overvoltage protection
- Silent operation
- Automatic safe switch of faulty or end of life tubes
- Suitable for DC operation

SEC107

Mftrs. List No.	Order Code	Price Each		
		1+	20+	40+
QFH14	1 14W SINGLE	<b>317-8936</b>		
QFH21	1 21W SINGLE	<b>317-8948</b>		
QFH28	1 28W SINGLE	<b>317-8950</b>		
QFH35	1 35W SINGLE	<b>317-8961</b>		
QFH214	2 14W TWIN	<b>317-8973</b>		
QFH221	2 21W TWIN	<b>317-8985</b>		
QFH228	2 28W TWIN	<b>317-8997</b>		
QFH235	2 35W TWIN	<b>317-9000</b>		

continued

## Volume Pricing

If your requirements exceed the quantities in this catalogue, please ring us on (65) 788 0200.

30

959

Lighting & Torches