

- Combination of lightness, strength and ease of application
- Ideal for heating, ventilation and light industrial applications
- Bright class 'O' facing
- Non-combustible, inorganic glass wool defined as mineral wool in **BS3533**
- Complies with the requirements of **BS3958:PART 4**, **BS5422** and **BS5970**
- Fire performance: non-combustible when tested in accordance with **BS476:PART 4:1970**
- Complies with class 'O' requirements of the building regulations when tested to **BS476:PARTS 6 & 7**.

Limiting temperature 230°C
 Thermal conductivity at 10°C 0.031 W/mK
 Thermal conductivity at 150°C 0.050 W/mK

ipp183

1.2m Length Pipe Ø	Mftrs. List No.	Order Code	1+	5+	10+	20+
15	C1525SA	719-2540				
21/22	C2125SA	719-2551				
27/28	C2725SA	719-2563				
34/35	C3425SA	719-2575				
42	C4225SA	719-2587				
48	C4825SA	719-2599				

Crown Pipe Insulation P.I.B. Covered



- Fibreglass insulation for use in external applications 25mm thick
- Retains the excellent insulation with the extra advantage of a factory applied flexible weatherproof finish
- The polyisobutylene (PIB) finish is 0.8mm thick and provides protection where the likelihood of mechanical damage is minimal
- Sections are supplied with a minimum of 25mm overlap to the longitudinal joint and 50mm wide cover strips for the circumferential butt joints
- All overlaps and cover strips to be carefully secured with Welding Agent so to prevent the ingress of moisture see Order Code **722-2210** for 5 Litre tin

Best Value

Limiting temperature 230°C
 Thermal conductivity at 10°C 0.031 W/(m.K)
 Thermal conductivity at 150°C 0.050 W/(m.K)
 Insulation thickness 25mm

ipp323

1.2m Length Pipe O/D mm	Order Code	1+	5+	10+	20+
15	722-2154				
21/22	722-2166				
27/28	722-2178				
34/35	722-2180				
42	722-2191				
48	722-2208				
Welding Agent		1+	5+	10+	20+
5 Litre Tin	722-2210				

Insulation Accessories

KITSONS
www.kitsons-products.co.uk



- Armaflex™ adhesive for securing and sealing joints on Armaflex™ and Tubolit™ Plus pipe sections
- PVC tape for taping joints on Armaflex™ and Tubolit Plus™ pipe sections
- Double-sided tape for installation of pipe line identification
- Spraytack is a general-purpose aerosol adhesive

ipp188

	Mftrs. List No.	Order Code	1+	5+	10+	20+
Adhesive Tape	AT05115M	719-2782				
Adhesive 250ml	AD520L16	719-2848				
Adhesive 0.5 litre	AD520L12	719-2850				
PVC Tape Black	752304	719-2861				
PVC Tape Grey	752310	719-2873				
Double-Sided Tape	751013	719-2885				
Spraytack Adhesive	718081	719-2897				

1/4" Group Couplings

Male Thread Coupling (Valved)



- 1/4" flow rate
- One hand operation
- All couplings have shut valve
- 120 psi (8.3 bar) working pressure
- Leak free O ring seal
- Hose barbs built in

Applications: water and compressed airlines, potable water, cooling lines, mild chemical handling beverage dispensing and vacuum lines.

Materials:

Body & Valves	Acetal
Internal Spring	316 Stainless Steel
External Spring pin	Stainless Steel
Latch	Stainless Steel
Seals	Buna - N
Colour	Natural White

Mftrs. List No. PLCD100-040BSPT = 719-6829, PLCD160-04 = 719-6842, PLCD170-04 = 719-6866, PLCD 100-060 BSPT = 719-6830, PLCD160-06 = 719-6854, PLCD170-06 = 719-6878

ipp318

Description	Order Code	1+	5+	10+	20+
1/4" BSPT male thread	719-6829				
3/8" BSPT male thread	719-6830				
1/4" hose barb PM	719-6842				
3/8" hose barb PM	719-6854				
1/4" hose barb	719-6866				
3/8" hose barb	719-6878				

Inserts (Valved)



ipp232

Description	Order Code	1+	5+	10+	20+
3/8" hose barb	719-7111				
1/4" BSPT male thread	719-7123				
3/8" BSPT male thread	719-7135				
1/4" hose barb PM	719-7147				
3/8" hose barb PM	719-7159				
1/4" hose barb	719-7100				

Insert (Unvalved)



Tom Parker Ltd

Acetal quick connect unvalved inserts

Mftrs. List No. PLC22004 = 719-7445, PLC240040BSPT = 719-7469, PLC22006 = 7197457, PLC240060BSPT = 719-7470

ipp235

Description	Order Code	1+	5+	10+	20+
1/4" Hose Barb	719-7445				
3/8" Hose Barb	719-7457				
1/4" BSPT Male Thread	719-7469				
3/8" BSPT Male Thread	719-7470				