


Power Toggle Switches — continued

600 Series.
15A @ 250V ac



Approved to **UL** and **CSA**.

Proof voltage	2500V rms
Electrical life	10000 operations
Insulation resistance	1000MΩ
Operating temperature	-20°C to +55°C
Initial contact resistance	10mΩ

Body: H = 15.0, W = 14.0, D = 29.5 (single pole)
 H = 21.5, W = 21.5, D = 29.7 (double pole)
 Toggle : L = 13.5 (insulated), L = 17.5 (metal)
 Bush : L = 11.5 (insulated), L = 10.5 (metal)
 Dia. = 12 0.75 Tabs : 6.35 0.8

Mfrs. List No.
 631NH/2 = 285-845, 636NH/2 = 285-857, 639NH/2 = 285-869, 641NH/2 = 285-870,
 646NH/2 = 285-882, 631H/2 = 285-894, 636H/2 = 285-900, 639H/2 = 285-912,
 641H/2 = 285-924, 646H/2 = 285-936, 649H/2 = 285-948, 649NH/2 = 607-447

SW207

Insulated Lever	Order Code	Price Each			
		1+	25+	100+	250+
SPST – on-off	285-845				
SPDT – on-on	285-857				
SPDT – on-off-on	285-869				
DPST – on-off	285-870				
DPDT – on-on	285-882				
DPDT – on-off-on	607-447				
Metal Lever					
SPST – on-off	285-894				
SPDT – on-on	285-900				
SPDT – on-off-on	285-912				
DPST – on-off	285-924				
DPDT – on-on	285-936				
DPDT – on-off-on	285-948				

IP67 Sealed
20A @ 250V ac or 30V dc



- Silver plated contacts.
- Sealed to **IP67**.
- Connections via 250 (1/4") receptacles or soldering.

H = 35, W = 19, D = 17.5 (body) Bush diameter = 11.4,
 Bush thread = M12 1.0, Bush length = 6.5

Mfrs List No: ATD15W = 918-313, ATE15W = 918-325,
 ATN15W = 918-337, ATRS15W = 918-349,
 ATP = 918-330, ATT15W = 918-362, AWTS15 = 918-374

SW123

	Order Code	Price Each				
		1+	10+	25+	100+	250+
SPDT – on-on	918-313					
SPDT – on-off-on	918-325					
DPDT – on-on	918-337					
DPDT – on-mom	918-349					
DPDT – on-off-on	918-350					
DPDT – on-off-mom	918-362					
DPDT – mom-off-mom	918-374					

IP67 Sealed – 3600 Series
20A @ 28V dc, 6A @ 220V ac



- Sealed to **IP67**, suitable for outdoor use

Proof voltage	2500V ac
Electrical life	1000 ops
Insulation resistance	1000MΩ @ 500V dc
Operating temperature	-40°C to +85°C

H = 35, W = 21.5, D = 23
 Bush thread = 12 0.75, Tabs = 6.35 0.8, Panel thickness = 5 max.

Mfrs. List No. 3631NF/2 = 219-356, 3636NF/2 = 219-368,
 3641NF/2 = 219-370, 3646NF/2 = 219-381

SW192

	Order Code	Price Each				
		1+	10+	25+	100+	250+
SPST – on-off	219-356					
SPDT – on-on	219-368					
DPST – on-off	219-370					
DPDT – on-on	219-381					

Accessories

Toggle Switch Cover



H = 25, Dia = 25

- Moulded black flexible PVC splashproof switch cover
- Nickel-plated brass threaded insert suitable for all 1/8" 32NS bush threads.



Mfrs. List No. SX0550/Brass

SW166

Order Code	Price Each				
	1+	50+	100+	500+	1000+
.151-352					

Toggle Switch Accessories

Suitable for all Bush Threads of 1/8" 32NS



140-648 678-144 678-156 140-663 140-658

Waterproof lever cover	A0331MO	140-648
Waterproof lever cover	A1080MO	678-144
Waterproof lever seal	A0539MO	678-156
Slotted knurled ring nut chrome finished, dia. = 16.0, thickness = 2.3	T92/Chrome	140-663
ON/OFF status plate chrome finished, 25.4 16 overall	P23/2	140-658

Mfrs. List No. Order Code

Order Multiple = 10	Order Code	Price Each					
		10+	50+	100+	250+	500+	1K+
140-648							
678-144							
678-156							
140-663							
140-658							

SW20

Toggle and Push Button Sealing Boots



Covered toggle seal 150-212
 Protruding toggle seal 150-213
 Push button seals 150-214 150-215

- Black silicone rubber sealing boots for most toggle and pushbutton switches
- Moulded-in brass, nickel plated hexagonal nut gives water-tight, dust-tight protection
- Provide low cost sealing for non-MIL spec applications
- Operating temperature -40°C to +85°C

Mfrs. List No. U1024 = 150-212, U1602 = 150-213, U1320 = 150-214,
 U590 = 150-215, U1231 = 607-459

SW140

Thread Size	Order Code	Price Each				
		1+	25+	100+	500+	1K+
Covered Toggle Seal						
11.9(1/2") 32NS	150-212					
6.35 (1/4") 40NS	607-459					
Protruding Toggle Seal						
11.9(1/2") 32NS	150-213					
Push Button Seals						
6.35(1/4") 40NS	150-214					
11.9(1/2") 32NS	150-215					

Toggle and Push Button Sealing Boots
'Hexseals' (MIL spec)



Covered toggle seals Protruding toggle seals Push button seals