Analogue Voltmeter

Analogue Meters — continued TENYA



A rugged multimeter ideal for either field or bench use 26 ranges, three coloured mirrored

- New
- scale AC/DC volts, DC current
- Resistance, continuity
- Transistor check
- Temperature check -51°C ~260°C
- Battery test, fuse and diode protection
- CE marked, meets IEC-1010-1
- Includes batteries and test leads

H = 177.8, W = 120, D = 32


Sensitivity 12V to 1000V AC volts 10ΩK/V +4% DC volts 0.6V to 1000V 30KΩ/V ±3% DC current 120uA to 10A +3% 0 to 50MΩ -10dB~ +62dB Resistance ±3° of arc. Decibels Power requirements 2 x AA and one 9V battery (included)

multimeter

Price Each Mftrs. List No. **Order Code** 3+ 5+ 72-6170 356-2608

Analogue Voltmeter 72-6171





TENMA

JIBRATION

SERVICES

- scale AC/DC volts, DC current
- Resistance, continuity
- 1.5V and 9V battery test
- Fuse and diode protection
- CE marked, meets IEC-1010-1
- Includes test leads and batteries

H = 143, W = 92, D = 2.3

Accuracy Sensitivity 10V-1000V 20KO/V +4% DC volts 2 5V-1000V DC current 5mA-10A Resistance $\begin{array}{l} 0\text{-}10\text{M}\Omega \\ \text{-}8\text{dB} \sim +62\text{dB} \\ 2 \text{ x AA (included)} \end{array}$ 4° of arc Power requirements

T558A **Price Each** Mftrs. List No. **Order Code** 1+ 3+ 5+ 72-6171 356-2610

MX1, MX2



- Heavy duty multimeters
- Rubberised cases to withstand shock and vibration sealed to IP65
- Large easy to use scales
- SECURX test lead locking mechanism
- High speed continuity beeper and diode test
- Audible warning on ohms ranges if more than 5 volts is applied to the input termi-
- Mains proof ohms range, 10KA fuse potection on current ranges
- MX2 supplied with current clamp for non intrusive measurement

voltage ranges from 150mV to 1000V 5 to 1000V 6 ac voltage ranges from resistance ranges 200Ω 2ΚΩ, 20kΩMX1 7 dc current ranges 50uA to 10A MX2 MX1 50μA to 10A 500mA to 10A 2 dc current ranges 6 ac current range MX2 4 ac current ranges via clamp adaptor

Price Each Mftrs List No. Order Code 5+ 10+ MX1 724-970‡ MX2 C 5 724-981‡ ‡ Subject to design change Fach S C5 **Standard Calibration Charge** 7

MX570

True rms Digital meter



melcix.

T343X

Digital Multimeter with analogue pointer

- SERVICES True analogue pointer with easy to read scale
- Auto/manual ranging on volts and ohms Display hold
- Rapid continuity test with beeper and diode test
- Separate displays, with the pointer showing actual input, while the digital readout records the Peak Value

dc Voltage	5 ranges	400mV to 1000V
ac Voltage	5 ranges	400mV to 750V
dc current	6 ranges	400μA to 10A
ac current	6 ranges	400μA to 10A
resistance	6 ranges	400Ω to $20m\Omega$

Price Each

T329

Mftrs. List No. **Order Code** 1+ 10+ 5+ MX570 C5 724-993

Each 7 Standard Calbration Charge

Digital Multimeters

Pen DMM with Logic Function 72-6620







The 72-6620 is a rugged, multi-featured, pen-type multimeter, ideal for taking measurements in tight spots, panels or enclosures.

- Large 3³/₄ digit, 3999 count LCD
- Autoranging with auto polarity
- Data hold
- Auto power off
- TTL logic test (Hi/Lo indicator)
- AC and DC voltage and current measurement

DC/AC voltage 4V. 40V. 600V

- Resistance with continuity beeper
- Fuse protected
- CE marked, meets IEC-1010 safety standards for 600V CAT II
- Includes 9V battery, ground lead, alligator clip, probe tip covers and owners manual

Resistance 400Ω~40MΩ

Dimensions 28.58 (W) x 228.6 (L) x 38.10 (H)

T576

Order Code 10+ 1+ 5+ 72-6620 342-1478



1546