

Mfrs. List No. 20067

T176

Order Code	Price Each			
	1+	5+	10+	25+
226-154				

## Test Clip Lead Kit



- A set of eight general purpose mini-hook test clips
- Good for both SMD and basic test inter-connection
- 500mm long PVC wire
- Set consists of two black, two red, one


green, one yellow, one blue and one white cord  
 ● 2A maximum 20V ac/60V dc



Order Code	Price Each		
	1+	5+	10+
76-004	342-1661		

T596

## Shrouded Probe Test Lead, 4mm Plug



A 1m long PVC test lead fitted at one end with a test probe having a spring loaded retractable transparent shroud shielding a combined 4mm plug style pointed probe tip. The other end of the test lead is fitted with a right angle fixed shroud 4mm plug having an insulated tip centre pin.

Working voltage 1000V, maximum current 32A.


Mfrs. List No. 20066-1 = 226-130, 20066-4 = 226-142

T178

Colour	Order Code	Price Each			
		1+	10+	25+	50+
Red	226-130				
Black	226-142				

## Test Lead Sets

### Shrouded Patch Cord, 4mm Plugs



Silicone rubber test leads available in 1.0m or 1.5m lengths terminated at each end with 4mm shrouded stackable plugs. Spring loaded shroud retracts when inserted.


Maximum current 5A.

Mfrs. List No. 0-1248850-1 = 143-984, 0-1248840-1 = 152-257, 0-1248850-2 = 143-985, 0-1248840-2 = 152-258

T57

Colour	Order Code	Price Each			
		1+	10+	25+	50+
<b>1.0m Length</b>					
Red	.152-258				
Black	.152-257				
<b>1.5m Length</b>					
Red	143-985				
Black	143-984				

## Stackable, 4mm Plugs



PVC test leads, 1m in length terminated at each end with 4mm gold plated hermaphrodite stackable plugs. Working voltage 240V ac. Maximum current 19A.

Mfrs. List No. 21.0830-1 = 152-748, 21.0830-4 = 152-749

T164

Colour	Order Code	Price Each		
		1+	10+	25+
Red	152-748			
Black	152-749			

## Stackable, 4mm Plugs




Injection-moulded PVC measuring lead with 4mm dia. shatter-proof connectors. Incorporates cage spring plugs and 4mm dia. sockets for stacking. Nickel-plated copper beryllium contact spring. Highly flexible, double insulated, 1mm<sup>2</sup> stranded lead. Working voltage 50V, Current 16A. Available in various lengths.

Mfrs. List No. ML + Length + Colour

T252

Length/Colour	Order Code	Price Each			
		1+	25+	50+	100+
<b>250mm</b>					
Red	523-689				
Black	523-690				
<b>500mm</b>					
Red	523-719				
Black	523-720				
Blue	523-732				
<b>1000mm</b>					
Red	523-744				
Black	523-756				
Blue	523-768				
<b>1500mm</b>					
Red	523-770				
Black	523-781				
Blue	523-793				
<b>2000mm</b>					
Red	523-800				
Black	523-811				

## Safety, Shrouded, 4mm Plugs 1000V



Flexible 1m length PVC connecting leads fitted with 4mm plugs. The slimline stackable plugs feature fixed shrouds and insulated tip centre pins for additional safety. Manufactured to IEC1010-1, VDE0100/0110, approved by BG. Working voltage 1000V, maximum current 32A.

Mfrs. List No. 21.5430-1 = 152-736, 21.5430-4 = 152-737

T159

Colour	Order Code	Price Each		
		1+	10+	25+
Red	152-736			
Black	152-737			

## Safety, In-Line Non Stackable, 4mm Plugs 1000V



Flexible, 1m length PVC connecting leads fitted with in-line style non-stackable 4mm plugs. Each plug features fixed shrouds and insulated tip centre pins for additional safety. Manufactured to IEC1010-1, VDE0100/0110, approved by BG. Working voltage 1000V, maximum current 32A.

Mfrs. List No. 21.5080-1 = 226-099, 21.5080-4 = 226-105

T180

Colour	Order Code	Price Each		
		1+	10+	50+
Red	226-099			
Black	226-105			

continued