

Test Lead Sets — continued

Right Angle/In-Line Non Stackable, 4mm Plugs



PVC test leads, 1m in length terminated with a 4mm right angle plug at one end and a 4mm in-line plug at the other. Each plug features fixed shrouds and insulated tip centre pins for additional safety.

Working voltage 1000V, maximum current 32A


Mfrs. List No. 21.3390-1 = 226-117, 21.3390-4 = 226-129

T179

Colour	Order Code	1+	10+	25+	50+
Red	226-117				
Black	226-129				

Cable length	Order Code	Price Each			
		1+	10+	25+	50+
<b>BNC Plug to BNC Plug</b>					
0.5m	315-3472				
1.0m	315-3484				
2.0m	315-3496				
<b>BNC Plug to Crocodile Clips</b>					
1.0m	315-3502				
<b>BNC Plug to 4mm Plugs</b>					
1.0m	315-3514				

Adaptor, 2mm to 4mm



PVC test lead adaptor, 300mm in length terminated with a 2mm plug at one end and a 4mm plug at the other. For convenience, gold plated hermaphrodite stackable plugs are fitted. The leads are suitable for converting and inter-connecting between either system. Working voltage 240V ac, maximum current 10A.

Mfrs. List No. 21.1620-1 = 152-752, 21.1620-4 = 152-753

FOR SEPARATE PLUG/SOCKET ADAPTORS SEE PAGE 507

T166

Colour	Order Code	1+	10+	25+
Red	152-752			
Black	152-753			

4mm Stacking Patch Cords



- 4mm stacking banana plugs
- Flexible silicone jacketed wire
- CE marked rated 1200V 12A



T573A

Mfrs. List No.	Order Code	1+	5+	10+
76-008 Red 40"	356-2426			
76-009 Black 40"	356-2438			
76-010 Red 60"	356-2440			
76-012 Black 60"	356-2451			

Cable Test Leads 50Ω



Ready-made test and interconnection leads using RG58 cable and fitted with moulded strain relief sleeves. Available in various cable lengths.

cr48